Epson EB-1485Fi data projector Ultra short throw projector 5000 ANSI lumens 3LCD 1080p (1920x1080) White

Brand : Epson **Product code:** V11H919040

Product name: EB-1485Fi

- Flexible display options and sizes: Cater for user needs in any working environment
- $\hbox{- All-in-one interactive meeting display: Combines multiple resources in one interactive collaboration device}\\$
- Increase productivity & agile working: Share and display content from a range of devices simultaneously
- Sliding split screen: Up to four displays in one image project images from different sources
- Easy installation: Quick set-up with auto-adjusting calibration function Laser, 3LCD, LCD Panel 0.62", 5000 Lumen, Full HD, 16:9, 2500000:1, 10 Bits, 192Hz-240Hz, Optical Lens, 8.68: 1, 366W, 9.8kg







Projector		Features	
Supported aspect ratios Screen size compatibility * Projection distance Projection distance (wide) Projection distance (tele) Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours	16:9 1651 - 2540 mm (65 - 100") 0 - 0.78 m 0 - 0.4 m 0 - 0.6 m 5000 ANSI lumens 3LCD 1080p (1920x1080) 2500000:1 16:9 1.07 billion colours	Interactive * Interactive input supported Noise level (economic mode) On Screen Display (OSD) Screen mirroring Noise level * Air filter Composite sync Country of origin Password protection	Interactive pen/Touch 27 dB
Projector brightness (economic mode) Vertical scan range	3500 ANSI lumens 192 - 240 Hz	Compatible operating systems	10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Ubuntu 14.10, Ubuntu 15.04, Windows 10, Windows 10 (32/64 bit), Windows 2000
Keystone correction, horizontal Keystone correction, vertical	-3 - 3° -3 - 3°	Multimedia	
Matrix size Heat dissipation	1.57 cm (0.62") 1244 BTU/h	Built-in speaker(s) * RMS rated power Number of built-in speakers	√ 16 W 2
Light source		Design	
Light source type * Service life of light source * Service life of light source (economic mode)	Laser 20000 h 30000 h	Market positioning * Product type * Product colour *	Business Ultra short throw projector White
Lens system		Placement	Wall
Focus * Fixed focal length	Manual 3.9 mm	Cable lock slot Cable lock slot type	√ Kensington
Zoom capability	1	Power	
Zoom type Zoom ratio Throw ratio	Auto 1.35:1 0.27 - 0.37:1	Power source * Power consumption (typical) * Power consumption (standby) *	AC 366 W 0.5 W
Video		Power consumption (economy mode)	262 W
Full HD * 3D * Supported graphics resolutions Supported video modes	✓ X 1920 x 1080 (HD 1080) 1080p	AC input voltage AC input frequency	220-240 V 50 - 60 Hz

Video		Software	
Video processing Video colour modes Adjustable colour temperature	10 bit Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode	Software support	via: AMX, Crestron (Network), Extron, Crestron (RS-232C only), Crestron Integrated Partner, Crestron RoomView, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol
Ports & interfaces HDMI connector type	Full-size	Windows operating systems	Windows 10, Windows 10 x64,
HDBaseT port	√	supported	Windows 2000
USB 2.0 ports quantity *	2	Operational conditions	
USB 2.0 Type-B ports quantity	2	Storage temperature (T-T)	-10 - 60 °C
Headphone outputs	1	Weight & dimensions	
Microphone in	✓	Width	458 mm
Serial interface type *	RS-232C	Depth	375 mm
PC Audio in	✓	Height	210 mm
PC Audio out	✓	Weight *	9.3 kg
VGA (D-Sub) ports quantity *	2	Package width	472 mm
HDMI ports quantity *	3	Package depth	590 mm
Component video (YPbPr/YCbCr) in *		Package height	640 mm
DVI port *	×	Package weight	27.7 kg
DC-in jack	✓	Packaging content	
Network		Remote control included *	1
Smart TV *	×	Batteries included	✓
Ethernet LAN *	✓	Cables included	AC
Wi-Fi *	√	Manual	✓
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Mounting brackets included	1
Miracast	✓ (001.11.1,) (001.11.11,)	AC adapter included	✓
	•	WLAN adapter included	✓
Storage Card reader integrated *	×	Bundled software	Easy Interactive Tools, EasyMP Multi PC Projection, Epson Projektor Management
		Technical details	
		Sustainability certificates	TCO
		Logistics data	
		Quantity per pack Products per pallet Pallet gross weight Products per pallet (UK) Pallet weight (UK) Harmonized System (HS) code	1 pc(s) 6 pc(s) 0 g 12 pc(s) 0 g 85286200
		Other features	
		Supported network protocols	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink



8715946674070

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.