



ATEN CS1716A-AT-G KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: CS1716A-AT-G

Tuotteen nimi : CS1716A-AT-G



ATEN CS1716A-AT-G. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: QXGA, Enimmäiserottelutarkkuus: 2048 x 1536 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metall. Voimanlähde: DC, Tulojännite: 5.3 V, Virrankulutus: 6,6 W. Vaatimustenmukaisuustodistukset: RoHS



Ports & interfaces		System requirements	
Number of computers controlled *	512	Linux operating systems supported	✓
Keyboard port type *	USB, PS/2	Mac operating systems supported	✓
Mouse port type *	USB, PS/2	Sustainability	
Video port type *	VGA	Compliance certificates	RoHS
VGA (D-Sub) ports quantity	17	Operational conditions	
Console ports *	USB A, VGA (D-Sub)	Operating temperature (T-T)	0 - 50 °C
Console USB ports quantity	1	Storage temperature (T-T)	-20 - 60 °C
DC-in jack	✓	Operating relative humidity (H-H)	0 - 80%
Performance		Weight & dimensions	
HD type *	QXGA	Width	437.2 mm
Maximum resolution *	2048 x 1536 pixels	Depth	159.9 mm
Scan interval	1,255 s	Height	44 mm
DDC2B support	✓	Weight	3.61 kg
Hot-Plug support	✓	Packaging data	
Daisy chain	✓	Package width	116 mm
Firmware upgradeable	✓	Package depth	540 mm
Design		Package height	233 mm
Rack mounting *	✓	Package weight	4 kg
Rack capacity	1U	Packaging content	
Product colour *	Black	Cables included	KVM
Housing material	Metal	Quick installation guide	✓
LED indicators	✓	AC adapter included	✓
Push button	✓	Rack mount kit	✓
Hot keys	✓	Logistics data	
Display		Master (outer) case net weight	10.8 kg
Built-in display *	✗	Harmonized System (HS) code	85176200
On Screen Display (OSD)	✓	Master (outer) case width	375 mm
Power		Master (outer) case length	565 mm
Power source	DC	Master (outer) case height	258 mm
Input voltage	5.3 V	Master (outer) case gross weight	12.6 kg
Power consumption (typical)	6.6 W	Products per master (outer) case	3 pc(s)

System requirements

Windows operating systems supported





4710423775329

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date