

ZYXEL

## Zyxel XS1930-12HP-ZZ0101F verkkokytkin Hallittu L3 10G Ethernet (100/1000/10000) Power over Ethernet -tuki musta

**Tuotemerkki :** Zyxel

**Tuotekoodi:** XS1930-12HP-ZZ0101F

**Tuotteen nimi :** XS1930-12HP-ZZ0101F



Zyxel XS1930-12HP-ZZ0101F. Kytkin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 10. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 240 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af,.... Power over Ethernet -tuki. Telineasennus

Management features		Design	
Switch type *	Managed	Product colour	Black
Switch layer	L3	LED indicators	✓
Quality of Service (QoS) support	✓	<b>Power</b>	
Web-based management	✓	Power supply included *	✓
Cloud-managed	✓	AC input voltage	100 - 240 V
Configuring Location Settings (CLI)	✓	AC input frequency	50 - 60 Hz
MIB support	✓	Power consumption (max)	493 W
Ports & interfaces		Power over Ethernet (PoE)	
Basic switching RJ-45 Ethernet ports quantity *	10	Power over Ethernet (PoE) *	✓
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Power over Ethernet plus (PoE+) ports quantity	8
SFP+ module slots quantity	2	Total Power over Ethernet (PoE) budget	375 W
Network		Operational conditions	
Networking standards *	IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3x	Operating temperature (T-T)	-20 - 50 °C
	10G support *	Storage temperature (T-T)	-40 - 70 °C
Port mirroring	✓	Operating relative humidity (H-H)	5 - 95%
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s	Storage relative humidity (H-H)	5 - 95%
VLAN support	✓	Heat dissipation	151.06 BTU/h
Data transmission		Weight & dimensions	
Switching capacity *	240 Gbit/s	Width	330 mm
MAC address table *	16000 entries	Depth	230 mm
		Height	44 mm
		Weight	2.8 kg
		Logistics data	
		Harmonized System (HS) code	85176990

**Multicast features**

Multicast support ✓

**Design**

Rack mounting \* ✓



4718937605262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date