Canon

Canon i-SENSYS LBP6030B 2400 x 600 DPI A4

Tuotemerkki : Canon   **Tuoteperhe:** i-SENSYS   **Tuotekoodi:** 8468B042

Tuotteen nimi : LBP6030B

Canon i-SENSYS LBP6030B. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 5000 sivua kuukaudessa. Suurin resoluutio: 2400 x 600 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 18 ppm. Tuotteen väri: musta

Printing

Colour *	✗
Print technology *	Laser
Duplex printing *	✗
Maximum resolution *	2400 x 600 DPI
Print speed (black, normal quality, A4/US Letter) *	18 ppm
Warm-up time	10 s
Time to first page (black, normal)	7.8 s
Print margins (top, bottom, right, left)	5 mm

Features

Maximum duty cycle *	5000 pages per month
Printing colours *	Black
Number of print cartridges *	1
Page description languages *	UFRII-LT

Input & output capacity

Total number of input trays *	1
Total input capacity *	150 sheets
Total output capacity *	100 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper, Transparencies
ISO A-series sizes (A0...A9) *	A4, A5
ISO B-series sizes (B0...B9)	B5
Envelopes sizes	C5, DL, Monarch
Custom media width	76.2 - 216 mm
Custom media length	188 - 356 mm
Multi-Purpose Tray media weight	60 - 163 g/m²

Ports & interfaces

Standard interfaces	USB 2.0
USB 2.0 ports quantity	1

Network

Wi-Fi *	✗
Ethernet LAN *	✗

Performance

Internal memory *	32 MB
Built-in processor	✗

Design

Product colour *	Black
Built-in display *	✗

Power

Power consumption (printing) *	330 W
Power consumption (max)	870 W
Power consumption (standby)	1.8 W
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

System requirements

Windows operating systems supported	✔
Mac operating systems supported	✔
Linux operating systems supported	✔
Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2

Operational conditions

Operating temperature (T-T)	10 - 30 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	364 mm
Depth	249 mm
Height	199 mm

Weight & dimensions	
Weight	5 kg
Logistics data	
Harmonized System (HS) code	84433210

8714574661445