

## Epson TM-L90LF (682): Serial, built-in USB, PS, EDG, Liner-free

**Tuotemerkki :** Epson

**Tuotekoodi:** C31C412682

**Tuotteen nimi :** TM-L90LF (682): Serial, built-in USB, PS, EDG, Liner-free



- Sisäänrakennettu tarran irrotusanturi: Automaattinen seuraavan tarran tulostus
- Monipuolinen materiaalienkäsittely: Materiaalien leveydet 3,81 cm, 5,08 cm ja 7,62 cm
- Nopeus: Tulostusnopeus jopa 170 mm/s
- Paperinsäästö: Entistä parempi paperinsäästötoiminto
- Helppo asentaa: Kolme asennustapaa

TM-L90LF (682): Serial, built-in USB, PS, EDG, Liner-free

Epson TM-L90LF (682): Serial, built-in USB, PS, EDG, Liner-free. Tulostustekniikka: Suoralämpö, Suurin resoluutio: 203 x 203 DPI, Tulostusnopeus: 90 mm/s. Tuetut paperin leveydet: 80 mm. Yhteysteknologia: Langallinen. Tuotteen väri: Harmaa

<b>Printing</b>		<b>Operational conditions</b>	
Print technology *	Direct thermal	Storage relative humidity (H-H)	10 - 90%
Maximum resolution *	203 x 203 DPI	Operating temperature (T-T)	5 - 45 °C
Print speed *	90 mm/sec	Storage temperature (T-T)	-10 - 50 °C
Printing characters	Text, Graphic	<b>Weight &amp; dimensions</b>	
<b>Paper handling</b>		Width	140 mm
Half-cutter	✓	Depth	148 mm
Maximum roll diameter	10.2 cm	Height	203 mm
Supported paper width	80 mm	Weight	1.9 kg
Autocutter durability	1 million cuts	<b>Packaging data</b>	
<b>Ports &amp; interfaces</b>		Quantity per pack	1 pc(s)
Connectivity technology *	Wired	Package width	195 mm
USB port *	✓	Package depth	255 mm
<b>Performance</b>		Package height	240 mm
Mean time between failures (MTBF)	360000 h	Package weight	2.76 kg
Mean cycles between failures (MCBF)	35000000	<b>Packaging content</b>	
Cutter	✓	Manual	✓
Certification	VCCI-Class A, CE	<b>Logistics data</b>	
<b>Design</b>		Products per pallet (UK)	168 pc(s)
Product colour *	Grey	Pallet weight (UK)	0 g
<b>Power</b>		Harmonized System (HS) code	84433210
AC input voltage	24 V	Pallet gross weight	0 g
Power consumption	1800 mA	Products per pallet	112 pc(s)
<b>Operational conditions</b>		<b>Other features</b>	
Operating relative humidity (H-H)	10 - 90%	Safety	TÜV
		Buffer size	4 KB
		Character sets	ANK
		Country of origin	China



8715946680163

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date