

## Samsung QE75T Digitaalinen litteä infotaulu 190,5 cm (75") LCD 300 cd/m<sup>2</sup> 4K Ultra HD musta Tizen 4.0

**Tuotemerkki** : Samsung

**Tuoteperhe**: QET

**Tuotekoodi**: LH75QETEPGCXEN

**Tuotteen nimi** : QE75T



Samsung QE75T. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 190,5 cm (75"), Näytön teknologia: LCD, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 300 cd/m<sup>2</sup>, HD-tyyppi: 4K Ultra HD. Käyttöjärjestelmä asennettu: Tizen 4.0. Tuotteen väri: musta

Display		Design	
LED backlight	✓	VESA mounting *	✓
Display diagonal *	190.5 cm (75")	Panel mounting interface	400 x 400 mm
Display technology *	LCD	Bezel colour	Black
Display resolution *	3840 x 2160 pixels	<b>Performance</b>	
Display brightness *	300 cd/m <sup>2</sup>	Purpose *	Commercial
HD type *	4K Ultra HD	HDCP	✓
Touchscreen *	✗	HDCP version	2.2
Response time	8 ms	<b>Power</b>	
Contrast ratio (typical)	1200:1	Power consumption (typical) *	253 W
Dynamic contrast ratio marketing name	Mega DCR	Power consumption (sleep)	0.5 W
Viewing angle, horizontal	89°	AC input voltage	100 - 240 V
Viewing angle, vertical	89°	AC input frequency	50/60 Hz
Pixel pitch	0.4296 x 0.4296 mm	Energy efficiency scale	A+++ to D
Display diagonal (metric)	189 cm	<b>Computer system</b>	
Horizontal scan range	15 - 135 kHz	Operating system installed	Tizen 4.0
Vertical scan range	24 - 75 Hz	<b>Weight &amp; dimensions</b>	
Haze rate	2%	Display width	1673.2 mm
Pixel frequency (max)	594 MHz	Display depth	59.9 mm
Colour gamut	72%	Display height	958.2 mm
<b>Ports &amp; interfaces</b>		Display weight	30.9 kg
HDMI ports quantity *	2	<b>Packaging data</b>	
HDMI version	2.0	Package width	1840 mm
HDMI input ports quantity	2	Package depth	198 mm
DVI port *	✗	Package height	1118 mm
USB port *	✓	Package weight	41.5 kg
USB ports quantity	1	<b>Operational conditions</b>	
Ethernet LAN *	✓	Operating temperature (T-T)	0 - 40 °C
Wi-Fi *	✗	Operating relative humidity (H-H)	10 - 80%
Audio (L/R) out	1	<b>Certificates</b>	
RS-232 interface	✓	Certification	Class B 60950-1
<b>Design</b>		<b>Other features</b>	
Product design *	Digital signage flat panel		
Placement supported *	Indoor		

Design		Other features	
Product colour *	Black	Annual energy consumption	250 kWh
Screen shape	Flat	Flash memory	8000 MB
		Energy efficiency class (old)	A
		Optional features	WMN4277SE



8806090557958

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date