



APC GVSUPS15KB2HS UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 15 kVA 15000 W

Tuotemerkki : APC

Tuotekoodi: GVSUPS15KB2HS


Tuotteen nimi : GVSUPS15KB2HS

APC GVSUPS15KB2HS. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 15 kVA, Lähtöteho: 15000 W. Pistorasian tyypit: Hard Wire 3-wire (3PH + G), Hard Wire 5-wire (3PH + N + G). Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 480 V. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LCD. Tuotteen leveys: 333 mm, Tuotteen syvyys: 847 mm, Tuotteen korkeus: 1485 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery voltage	480 V
Output power capacity *	15 kVA	Design	
Output power *	15000 W	Form factor *	Tower
Waveform *	Sine	Product colour *	White
Input operation voltage (min) *	340 V	Display type	LCD
Input operation voltage (max) *	460 V	International Protection (IP) code	IP20
Input frequency *	40/70 Hz	Certification	CSA C22.2 NO. 107.3, EN/IEC 62040-1, EN/IEC 62040-2, EN/IEC 62040-3, IEC 60721-4-2 Level 2M2, UL 1778 5th edition
Output operation voltage (min)	380 V	Operational conditions	
Output operation voltage (max)	415 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 40 °C
Maximum current	27 A	Operating relative humidity (H-H)	0 - 95%
Number of input phases	3	Storage relative humidity (H-H)	10 - 80%
Number of output phases	3	Operating altitude	0 - 1000 m
Input power factor	0.99	Non-operating altitude	0 - 3000 m
Crest factor	2.5:1	Weight & dimensions	
ECO mode	✓	Width	333 mm
Output voltage Total Harmonic Distortion (THD)	3%	Depth	847 mm
Input current Total Harmonic Distortion (THD)	3%	Height	1485 mm
Noise level	65 dB	Weight	245 kg
Power protection features	Overload, Short circuit	Package width	640 mm
Audible alarm(s)	✓		

Ports & interfaces		Weight & dimensions	
AC outlet types	Hard Wire 3-wire (3PH + G), Hard Wire 5-wire (3PH + N + G)	Package depth	990 mm
SmartSlot	✓	Package height	1690 mm
		Package weight	270 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85078000



0731304406716



731304406716

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.