



## APC KVM1116R KVM switch Rack mounting Black

Brand : APC

Product code: KVM1116R

Product name : KVM1116R



KVM 2G, Digital/IP, 1 Remote/1 Local User, 16 Ports with Virtual Media - FIPS 140-2

APC KVM1116R KVM switch Rack mounting Black:

Occupies 1U of rack space  
Conserve valuable rack space in the data center.

Hot Pluggable Operation  
Add or remove servers without having to power off the switch.

Multi-platform Support  
Windows, Sun, Unix and Linux compatible.

Scalable Architecture  
Cascade multiple KVM switches for a modular solution that supports multiple platforms, improving flexibility and simplifying future expansion. Please see the user's manual for specific cascading capabilities.

Out-of-band management  
Troubleshoot servers and diagnose problems in lieu of a working operating system with POST and BIOS-level access to servers.

Multi-platform Support  
Windows, Sun, Unix and Linux compatible.

Scalable Architecture  
Cascade multiple KVM switches for a modular solution that supports multiple platforms, improving flexibility and simplifying future expansion. Please see the user's manual for specific cascading capabilities.



Ports & interfaces		Sustainability	
Number of computers controlled *	16	Compliance certificates	RoHS
Keyboard port type *	PS/2	<b>Operational conditions</b>	
Mouse port type *	PS/2	Operating temperature (T-T)	0 - 50 °C
Video port type *	VGA	Storage temperature (T-T)	-20 - 60 °C
VGA (D-Sub) ports quantity	1	Operating relative humidity (H-H)	0 - 80%
<b>Network</b>		Storage relative humidity (H-H)	0 - 80%
Ethernet LAN	✓	<b>Weight &amp; dimensions</b>	
Ethernet LAN (RJ-45) ports	1	Width	424 mm
<b>Design</b>		Depth	188 mm
Rack mounting *	✓	Height	43 mm
Rack capacity	1U	Weight	2.59 kg
Product colour *	Black	<b>Packaging data</b>	
Certification	C-tick, CE, EAC, FCC Part 15 Class A, ICES-003, TAA compliance, UL-AR, UL 60950-1, VCCI Class A, VDE	Package width	619 mm
<b>Display</b>		Package depth	330 mm
Built-in display *	✗	Package height	146 mm
<b>Power</b>		Package weight	3.99 kg
AC input frequency	50 - 60 Hz	<b>Logistics data</b>	
		Harmonized System (HS) code	85176200



0731304340195



731304340195

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.