/isus

## ASUS ProArt PA248QV tietokoneen litteä näyttö 61,2 cm (24.1") 1920 x 1200 pikseliä WUXGA LED musta

Tuotemerkki : ASUS

Tuoteperhe: ProArt

Tuotekoodi: 90LM05K1-B01370

## Tuotteen nimi : PA248QV

ASUS ProArt PA248QV. Näytön halkaisija: 61,2 cm (24.1"), Näytön erottelutarkkuus: 1920 x 1200 pikseliä, HD-tyyppi: WUXGA, Näytön teknologia: LED, Näytön pinta: Matta, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:10, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





Display		Ports & interfaces	
Display diagonal *	61.2 cm (24.1")	Headphone outputs	1
Display resolution *	1920 x 1200 pixels	Headphone connectivity	3.5 mm
HD type *	WUXGA	HDCP	1
Native aspect ratio *	16:10	Ergonomics	
Display technology * Panel type *	LED IPS	VESA mounting *	1
Touchscreen *	×	Panel mounting interface	100 x 100 mm
	300 cd/m <sup>2</sup>	Cable lock slot *	1
Display brightness (typical) Response time *	5 ms	Cable lock slot type	Kensington
Display surface	Matt	Height adjustment *	<ul> <li>Image: A second s</li></ul>
Screen shape *	Flat	Adjustable height (max)	13 cm
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 720 x 480, 720 x 576, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768	Pivot	1
		Pivot angle	-90 - 90°
		Swivelling	1
		Swivel angle range	-90 - 90°
	(WXGA), 1280 x 800 (WXGA), 1280 x 960, 1440 x 900 (WXGA+), 1680 x	Tilt adjustment	1
	1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Tilt angle range	-5 - 35°
Supported video modes	480p, 576p, 720p, 1080p	On Screen Display (OSD)	1
Contrast ratio (typical) *	1000:1		Simplified Chinese, Traditional
Contrast ratio (dynamic)	10000000:1		Chinese, Croatian, Czech, German, Dutch, English, Spanish, French,
Dynamic contrast ratio marketing name	SmartContrast	On Screen Display (OSD) languages	Hungarian, Indonesian, Italian, Japanese, Korean, Polish,
Maximum refresh rate *	75 Hz		Portuguese, Romanian, Russian, Thai, Turkish
Viewing angle, horizontal	178°	Number of OSD languages	21
Viewing angle, vertical	178°	LED indicators	1
Display number of colours *	16.78 million colours	Power	
Pixel pitch	0.27 x 0.27 mm		-
Viewable size, horizontal	51.8 cm	Energy efficiency class (SDR) *	G

Display		Power	
Viewable size, vertical	32.4 cm	Energy consumption (SDR) per 100 hours *	<sup>0</sup> 28 kWh
Viewable size diagonal	61.1 cm 30 - 105 kHz	Power consumption (typical) *	28.2 W
Digital horizontal frequency Digital vertical frequency	49 - 75 Hz	Power consumption (standby) *	0.5 W
Colour gamut standard	sRGB	Power consumption (off)	0.3 W
sRGB coverage (typical)	100%	AC input voltage	100 - 240 V
	10070	AC input frequency	50 - 60 Hz
Performance		Energy efficiency scale	A to G
NVIDIA G-SYNC *	×	European Product Registry for	387772
AMD FreeSync *	×	Energy Labelling (EPREL) code	
VESA Adaptive Sync support	<ul> <li>Image: A set of the set of the</li></ul>	Operational conditions	
Flicker-free technology	<ul> <li>Image: A set of the set of the</li></ul>	Operating temperature (T-T)	0 - 40 °C
Low Blue Light technology	v	Storage temperature (T-T)	-20 - 60 °C
Multimedia		Weight & dimensions	
Number of speakers	2	Width (with stand)	533 mm
RMS rated power	- 4 W	Depth (with stand)	211 mm
Built-in speaker(s) *	· · · · · · · · · · · · · · · · · · ·	Height (with stand)	505 mm
Built-in camera *	×	Weight (with stand)	6.1 kg
	^	Width (without stand)	533 mm
Design		Depth (without stand)	47 mm
Market positioning *	Graphics design	Height (without stand)	360 mm
Product colour *	Black	Weight (without stand)	3.9 kg
Frameless design		Packaging data	
Feet colour	Black	Package width	649 mm
Ports & interfaces		Package depth	192 mm
Built-in USB hub *	✓	Package height	474 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package weight	8.3 kg
Number of upstream ports	1	Packaging content	
USB Type-A downstream ports quantity	4	Stand included	✓
VGA (D-Sub) ports quantity	1	Cables included	AC
DVI port	×	Other features	
HDMI *	1		UL/cUL, FCC, ICES-3, CB, ErP, WEEE,
HDMI ports quantity	1		TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI,
HDMI version	1.4	Certification	RCM, MEPS, VCCI, PSE, PC Recycle,
DisplayPorts quantity	1		J-MOSS, KC, KCC, e-Standby, Energy Star 8.0, TCO
DisplayPort version	1.2		
Audio input	1	Logistics data	
Headphone out *	1	Harmonized System (HS) code	85285210











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.