ASUS ProArt PA248QV tietokoneen litteä näyttö 61,2 cm (24.1") 1920 x 1200 pikseliä WUXGA LED musta

Tuotemerkki : ASUS Tuoteperhe: ProArt Tuotekoodi: 90LM05K1-

B01370

Tuotteen nimi: PA248QV

ASUS ProArt PA248QV. Näytön halkaisija: 61,2 cm (24.1"), Näytön erottelutarkkuus: 1920 x 1200 pikseliä, HD-tyyppi: WUXGA, Näytön teknologia: LED, Näytön pinta: Matta, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:10, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





Display		Ports & interfaces	
Display diagonal * Display resolution * HD type *	61.2 cm (24.1") 1920 x 1200 pixels WUXGA	Headphone outputs Headphone connectivity HDCP	1 3.5 mm ✓
Native aspect ratio *	16:10	Ergonomics	
Display technology * Panel type *	LED IPS	VESA mounting *	✓
Touchscreen *	X	Panel mounting interface	100 x 100 mm
Display brightness (typical)	300 cd/m ²	Cable lock slot *	✓
Response time *	5 ms	Cable lock slot type	Kensington
Display surface	Matt	Height adjustment *	✓
Screen shape *	Flat	Height adjustment	13 cm
	640 x 480 (VGA), 720 x 400, 720 x	Pivot	✓
	480, 720 x 576, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152	Pivot angle	-90 - 90°
Supported graphics resolutions	x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Swivelling	✓
		Swivel angle range	-90 - 90°
		Tilt adjustment	✓
		Tilt angle range	-5 - 35°
Supported video modes	480p, 576p, 720p, 1080p	On Screen Display (OSD)	
Contrast ratio (typical) *	1000:1		Simplified Chinese, Traditional Chinese, Croatian, Czech, German,
Contrast ratio (dynamic)	100000000:1	On Screen Display (OSD) languages	Dutch, English, Spanish, French, Hungarian, Indonesian, Italian, Japanese, Korean, Polish,
Dynamic contrast ratio marketing name	SmartContrast		
Maximum refresh rate *	75 Hz		Portuguese, Romanian, Russian, Thai, Turkish
Viewing angle, horizontal	178°	Number of OSD languages	21
Viewing angle, vertical	178°	LED indicators	✓
Display number of colours * Pixel pitch	16.78 million colours 0.27 x 0.27 mm	Power	
Viewable size, horizontal	51.8 cm	Energy efficiency class (SDR) *	G
Fichable Size, Horizontal	3210 0111		-

Display		Power	
Viewable size, vertical Viewable size diagonal Digital horizontal frequency Digital vertical frequency Colour gamut standard sRGB coverage (typical)	32.4 cm 61.1 cm 30 - 105 kHz 49 - 75 Hz sRGB 100%	Energy consumption (SDR) per 100 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (off) AC input voltage	28.2 W 0.5 W 0.3 W 100 - 240 V
Performance		AC input frequency Energy efficiency scale	50 - 60 Hz A to G
NVIDIA G-SYNC * AMD FreeSync *	× ×	European Product Registry for Energy Labelling (EPREL) code	387772
VESA Adaptive Sync support	✓	Operational conditions	
Flicker-free technology Low Blue Light technology	<i>y</i>	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Multimedia		Weight & dimensions	
Number of speakers RMS rated power Built-in speaker(s) * Built-in camera *	2 4 W •	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand)	533 mm 211 mm 505 mm 6.1 kg 533 mm
Design		Depth (without stand)	47 mm
Market positioning * Product colour *	Graphics design Black	Height (without stand) Weight (without stand)	360 mm 3.9 kg
Frameless design	✓	Packaging data	
Feet colour	Black	Package width	649 mm
Ports & interfaces		Package depth Package height	192 mm 474 mm
Built-in USB hub * USB hub version	2.2 Can 1 (2.1 Can 1)	Package weight	8.3 kg
Number of upstream ports	3.2 Gen 1 (3.1 Gen 1) 1	Packaging content	
USB Type-A downstream ports quantity	4	Stand included	✓ AC
VGA (D-Sub) ports quantity	1	Cables included	AC
DVI port	×	Other features	
HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version	1 1.4 1 1.2	Certification	UL/cUL, FCC, ICES-3, CB, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, Energy Star 8.0, TCO
Audio input	1.2 ✓	Logistics data	
Headphone out *	<i>✓</i>	Harmonized System (HS) code	85285210











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.