ASUS BE24EQSB tietokoneen litteä näyttö 60,5 cm (23.8") 1920 x 1080 pikseliä Full HD LED musta

Tuotemerkki : ASUS   **Tuotekoodi:** 90LM05M1-B02370

Tuotteen nimi : BE24EQSB

ASUS BE24EQSB. Näytön halkaisija: 60,5 cm (23.8"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta

Display

Display diagonal *	60.5 cm (23.8")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✗
Display brightness (typical)	300 cd/m²
Response time *	5 ms
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1280 x 960, 1366 x 768, 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)
Supported video modes	480p, 576p, 720p, 1080p
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	100000000:1
Dynamic contrast ratio marketing name	SmartContrast
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 million colours
Pixel pitch	0.275 x 0.275 mm
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Viewable size diagonal	60.5 cm
Digital horizontal frequency	55 - 96 kHz
Digital vertical frequency	48 - 77 Hz
NTSC coverage (typical)	72%

Ports & interfaces

AC (power) in	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	13 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt adjustment	✔
Tilt angle range	-5 - 35°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, French, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Romanian, Russian, Thai, Turkish
Number of OSD languages	21
LED indicators	Power, Stand-by

Power

Energy efficiency class (SDR) *	F
Energy consumption (SDR) per 1000 hours *	22 kWh
Power consumption (typical) *	21.7 W
Power consumption (standby) *	0.5 W

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Number of speakers	2
RMS rated power	4 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design

Market positioning *	Business
Product colour *	Black
Frameless design	✔
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
USB Type-A downstream ports quantity	4
VGA (D-Sub) ports quantity	1
DVI port	✘
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	✔
Headphone out *	✔
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	✔

Power

Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	405438

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Weight & dimensions

Width (with stand)	540 mm
Depth (with stand)	211 mm
Height (with stand)	332 mm
Weight (with stand)	7.8 kg
Width (without stand)	540 mm
Depth (without stand)	47 mm
Height (without stand)	330 mm
Weight (without stand)	5 kg

Packaging data

Package width	649 mm
Package depth	192 mm
Package height	474 mm
Package weight	10.5 kg

Packaging content

Stand included	✔
Cables included	AC, USB

Other features

Certification	Energy Star, BSMI, CB, CCC, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, TUV-Ergo, TUV-GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8, Windows 7), RCM, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, TCO, ICES-3, PC recycle

Logistics data

Harmonized System (HS) code	85285210

4718017562782