ASUS BE24EQSB tietokoneen litteä näyttö 60,5 cm (23.8") 1920 x 1080 pikseliä Full HD LED musta

Tuotemerkki : ASUS Tuotekoodi: 90LM05M1-B02370

Tuotteen nimi: BE24EQSB

ASUS BE24EQSB. Näytön halkaisija: 60,5 cm (23.8"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HDtyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	AC (power) in	✓
Display resolution * HD type *	1920 x 1080 pixels Full HD	Ergonomics	
Native aspect ratio *	16:9	VESA mounting *	✓
Display technology *	LED	Panel mounting interface	100 x 100 mm
Panel type *	IPS	Cable lock slot *	✓
Touchscreen *	×	Cable lock slot type	Kensington
Display brightness (typical)	300 cd/m ²	Height adjustment *	✓
Response time *	5 ms	Adjustable height (max)	13 cm
Screen shape *	Flat	Pivot	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1280 x 960, 1366 x 768, 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x	Pivot angle	-90 - 90°
		Swivelling	✓
		Swivel angle range	-180 - 180°
		Tilt adjustment	✓
		Tilt angle range	-5 - 35°
	1080 (HD 1080)	On Screen Display (OSD)	✓
Supported video modes	480p, 576p, 720p, 1080p		Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, French, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Romanian, Russian,
Contrast ratio (typical) *	1000:1		
Contrast ratio (dynamic) Dynamic contrast ratio marketing name	100000000:1 SmartContrast	On Screen Display (OSD) languages	
Viewing angle, horizontal	178°		Thai, Turkish
Viewing angle, vertical	178°	Number of OSD languages	21
Display number of colours *	16.78 million colours	LED indicators	Power, Stand-by
Pixel pitch	0.275 x 0.275 mm	Power	
Viewable size, horizontal	52.7 cm	Energy efficiency class (SDR) *	F
Viewable size, vertical Viewable size diagonal	29.6 cm 60.5 cm	Energy consumption (SDR) per 1000 hours *	22 kWh
Digital horizontal frequency	55 - 96 kHz	Power consumption (typical) *	21.7 W
Digital vertical frequency	48 - 77 Hz	Power consumption (standby) *	0.5 W
NTSC coverage (typical)	72%		

Performance		Power	
NVIDIA G-SYNC *	×	Power consumption (off)	0.3 W
AMD FreeSync *	×	AC input voltage	100 - 240 V
Flicker-free technology	✓	AC input frequency	50 - 60 Hz
Low Blue Light technology	✓	Energy efficiency scale	A to G
Multimedia		European Product Registry for Energy Labelling (EPREL) code	405438
Number of speakers	2	Operational conditions	
RMS rated power	4 W	Operating temperature (T-T)	0 - 40 °C
Built-in speaker(s) *	✓	Storage temperature (T-T)	-20 - 60 °C
Built-in camera *	x	Weight & dimensions	
Design		Width (with stand)	540 mm
Market positioning *	Business	Depth (with stand)	211 mm
Product colour *	Black	Height (with stand)	332 mm
Frameless design	✓	Weight (with stand)	7.8 kg
Feet colour	Black	Width (without stand)	540 mm
Ports & interfaces		Depth (without stand)	47 mm
		Height (without stand)	330 mm
Built-in USB hub *	22 (** 1 /21 (** 1)	Weight (without stand)	5 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Packaging data	
USB upstream port type USB Type-A downstream ports	USB Type-B	Package width	649 mm
quantity	4	Package depth	192 mm
VGA (D-Sub) ports quantity	1	Package height	474 mm
DVI port	X	Package weight	10.5 kg
HDMI *	✓	Packaging content	
HDMI ports quantity	1	Stand included	✓
HDMI version	1.4	Cables included	AC, USB
DisplayPorts quantity	1	Other features	
DisplayPort version	1.2		Energy Star, BSMI, CB, CCC, CEL
Audio input	✓		level , CU, ErP, FCC, ISO-9241-307,
Headphone out *	✓		J-MOSS, KCC, PSE, TUV-Ergo, TUV-
Headphone outputs	1	Certification	GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8,
Headphone connectivity	3.5 mm		Windows 7), RCM, TUV Flicker-free ,
HDCP	✓		KC , eStandby, TUV Low Blue Light, TCO, ICES-3, PC recycle
		Logistics data	
		Harmonized System (HS) code	85285210



4718017562782

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.