

## Chieftec Polaris virtalähdeyksikkö 550 W 20+4 pin ATX PS/2 musta

**Tuotemerkki :** Chieftec

**Tuoteperhe:** Polaris

**Tuotekoodi:** PPS-550FC

**Tuotteen nimi :** Polaris

Chieftec Polaris . Kokonaisteho: 550 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 150,450 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: PS/2, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 87 mm



<b>Power</b>		<b>Ports &amp; interfaces</b>	
Total power *	550 W	PCI Express power cable length	50 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	65 cm
Input current	8 A	Floppy drive power connector	1
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	✓
Combined power (+3.3V)	105 W	Cabling type	Fully-Modular
Combined power (+12V)	550 W	<b>Performance</b>	
Combined power (+5V)	105 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	PS/2
Max output current (+3.3V)	20 A	ATX version	2.4
Max output current (+12V)	45.8 A	<b>Design</b>	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	3 A	Fan diameter	12 cm
Power protection features	Over current, Over voltage, Overheating, Overload, Short circuit, Under voltage	Number of fans	1 fan(s)
<b>Ports &amp; interfaces</b>		Fan location	Top
Motherboard power connector *	20+4 pin ATX	<b>Weight &amp; dimensions</b>	
Motherboard power cable length	65 cm	Width	150 mm
Number of SATA power connectors	6	Depth	140 mm
SATA power cable length	150,450 mm	Height	87 mm
Peripheral (Molex) power connectors (4-pin) *	3	Weight	2.02 kg
Peripheral (Molex) power cable length	150,450 mm	<b>Packaging data</b>	
PCI Express power connectors (6+2 pin)	2	Package weight	2.33 kg
		Package type	Box

**Technical details**

Compliance certificates	RoHS
-------------------------	------

**Logistics data**

Harmonized System (HS) code	84733020
-----------------------------	----------



0753263076427



753263076427

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.