

Lexmark MX431adn Laser A4 600 x 600 DPI 40 ppm

Tuotemerkki : Lexmark

Tuotekoodi: 29S0211

Tuotteen nimi : MX431adn

Lexmark MX431adn. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 600 x 600 DPI. Kopiointi: Yksittäiskopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Yksittäisfaksin lähetyks. Suurin ISO A-luokan paperikoko: A4. Tuotteen väri: musta, Valkoinen



| | | | |
|---|------------------------------|---|--|
| Printing | | Network | |
| Duplex printing mode | Auto | Cabling technology | 10/100/1000Base-T(X) |
| Print technology * | Laser | Ethernet LAN data rates | 10,100,1000 Mbit/s |
| Printing * | Mono printing | Security algorithms | LEAP, MD5, MSCHAPv2, PEAP, SSL/TLS, TLS |
| Duplex printing * | ✓ | Supported network protocols (IPv4) | IPSEC, TCP/IP, ICMP, TCP, IGMP, UDP, 802.1x |
| Maximum resolution * | 600 x 600 DPI | Supported network protocols (IPv6) | IPSEC, TCP/IP, ICMP, TCP, IGMP, UDP, 802.1x |
| Print speed (black, normal quality, A4/US Letter) * | 40 ppm | Management protocols | DHCP, BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), SMTP, Finger |
| Time to first page (black, normal) | 5.9 s | Performance | |
| Copying | | Maximum internal memory | 512 MB |
| Duplex copying * | ✓ | Card reader integrated | ✗ |
| Duplex copying mode | Auto | Internal memory * | 512 MB |
| Copying * | Mono copying | Built-in processor | ✓ |
| Copy speed (black, normal quality, A4) | 39 cpm | Processor frequency | 1000 MHz |
| Time to first copy (black, normal) | 5.9 s | Processor cores | 2 |
| Copier resize | 25 - 400% | Sound pressure level (printing) | 53 dB |
| Scanning | | Sound pressure level (copying) | 54 dB |
| Duplex scanning * | ✓ | Sound pressure level (scanning) | 55 dB |
| Duplex scanning mode | Auto | Sound pressure level (standby) | 14 dB |
| Scanning * | Colour scanning | Design | |
| Optical scanning resolution * | 600 x 600 DPI | Product colour * | Black, White |
| Maximum scan area | 215.9 x 355.6 mm | Market positioning * | Business |
| Scanner type * | Flatbed & ADF scanner | Built-in display * | ✓ |
| Scan technology | CIS | Display | LCD |
| Scan to | E-mail, FTP, HTTP, LDSS, USB | Display diagonal | 7.11 cm (2.8") |
| Scan speed (colour) | 22 ppm | Control type | Touch |
| Scan speed (black) | 45 ppm | Power | |
| Duplex scan speed (colour) | 42 ppm | Power consumption (printing) | 580 W |
| Duplex scan speed (black) | 96 ppm | Power consumption (standby) | 0.1 W |
| Image formats supported | JPEG, JPG, TIFF | Power consumption (sleep) | 0.9 W |
| Document formats supported | PDF, XPS | Energy Star Typical Electricity Consumption (TEC) | 0.47 kWh/week |
| Fax | | System requirements | |
| Faxing * | Mono faxing | Windows operating systems supported | Windows 10, Windows 7, Windows 8, Windows 8.1 |
| Fax transmission speed | 3 sec/page | | |
| Modem speed | 33.6 Kbit/s | | |
| Features | | | |
| Recommended duty cycle | 800 - 8000 pages per month | | |
| Maximum duty cycle * | 80000 pages per month | | |
| Number of print cartridges * | 1 | | |

| Features | | System requirements | |
|---|--|-------------------------------------|--|
| Printing colours * | Black | Linux operating systems supported | Fedora 27, Linpus Linux 9.6, Ubuntu 16.04, Ubuntu 18.04 LTS, openSUSE 42.3 |
| Page description languages | PCL 5c, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3 | Server operating systems supported | SUSE Linux Enterprise Server, Windows 2000 Server, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2 |
| Country of origin | China | Other operating systems supported | Novell Open Enterprise Server 2 |
| Input & output capacity | | Operational conditions | |
| Total number of input trays * | 2 | Operating relative humidity (H-H) | 8 - 80% |
| Total input capacity * | 350 sheets | Operating temperature (T-T) | 10 - 32 °C |
| Total output capacity * | 150 sheets | Operating altitude | 0 - 2896 m |
| Paper tray 1 input capacity | 250 sheets | Certificates | |
| Multi-Purpose tray | ✓ | Certification | ICES-003 B, BSMI B, US FDA, UL 60950-1, FCC B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC, UL GS, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, DE-UZ 205, CGP |
| Multi-Purpose tray input capacity | 100 sheets | | |
| Auto document feeder (ADF) | ✓ | | |
| Auto document feeder (ADF) input capacity | 50 sheets | | |
| Maximum number of input trays | 3 | | |
| Maximum input capacity | 900 sheets | | |
| Paper handling | | Sustainability | |
| Maximum ISO A-series paper size * | A4 | Sustainability certificates | ENERGY STAR |
| Paper tray media types * | Card stock, Envelopes, Labels, Plain paper | Weight & dimensions | |
| ISO A-series sizes (A0...A9) * | A4, A5, A6 | Width | 411 mm |
| Non-ISO print media sizes | Executive, Folio, Legal, Letter, Oficio, Statement | Depth | 366 mm |
| Envelopes sizes | 9, 10, DL | Height | 339 mm |
| Paper tray media weight | 60 - 120 g/m ² | Weight | 12.8 kg |
| Multi-Purpose Tray media weight | 60 - 217 g/m ² | Packaging data | |
| Ports & interfaces | | Package width | 420 mm |
| Direct printing * | ✗ | Package depth | 465 mm |
| USB port | ✓ | Package height | 385 mm |
| USB connector | USB Type-B | Package weight | 14.7 kg |
| Network | | Packaging content | |
| Wi-Fi * | ✗ | Cartridge(s) included | ✓ |
| Ethernet LAN * | ✓ | Included cartridge capacity (black) | 3000 pages |
| | | Cables included | AC |



0734646701440



734646701440

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.