Lexmark MX522adhe Laser A4 1200 x 1200 DPI 44 ppm

Brand : Lexmark **Product code:** 36S0847

Product name: MX522adhe

Lexmark MX522adhe. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying. Scanning: Colour scanning. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey

Printing		Performance	
Print technology *	Laser	Maximum internal memory	2048 MB
Printing *	Mono printing	Card reader integrated	✓
Duplex printing *	✓	Internal memory *	2048 MB
Maximum resolution *	1200 x 1200 DPI	Built-in processor	✓
Print speed (black, normal quality, A4/US Letter) *	44 ppm	Processor frequency Processor cores	1200 MHz 4
Duplex print speed (black, normal quality, A4/US Letter)	23 ppm	Sound pressure level (printing)	56 dB
Time to first page (black, normal)	6 s	Sound pressure level (duplex printing)	55 dB
Print margins (top, bottom, right, left)	4 mm	Sound pressure level (copying)	56 dB
Copying		Sound pressure level (scanning) Sound power level (standby)	55 dB 14 dB
Duplex copying *	1		17 UD
Copying *	Mono copying	Design	
Copy speed (black, normal quality, A4)	44 cpm	Product colour * Market positioning *	Black, Grey Business
Time to first copy (black, normal)	6 s	Built-in display *	✓
Copier resize	25 - 400%	Display diagonal	10.9 cm (4.3")
Scanning		Touchscreen	✓
J	Cala	Control type	Touch
Scanning *	Colour scanning	Colour display	✓
Optical scanning resolution (black) Optical scanning resolution (colour)	1200 x 600 ppi 600 x 600 ppi	Power	
Maximum scan resolution	1200 x 600 DPI		620 W
Maximum scan area	215.9 x 355.6 mm	Power consumption (max)	630 W
Scanner type *	Flatbed & ADF scanner	Power consumption (average operating)	620 W
Scan technology	CIS	Power consumption (printing)	620 W
Scan to	E-mail, FTP, PC, USB	Power consumption (copying)	630 W
Scan speed (colour)	22 ppm	Power consumption (scanning)	20 W
Scan speed (black)	42 ppm	Power consumption (ready)	14.5 W
Duplex scan speed (colour)	44 ppm	Power consumption (sleep)	2.6 W
Duplex scan speed (black)	84 ppm	Power consumption (off)	0.1 W
Image formats supported Document formats supported	JPEG, JPG, TIFF PDF, XPS	Energy Star Typical Electricity Consumption (TEC)	1.9 kWh/week
Fax		System requirements	
Duplex faxing	✓	Windows operating systems supported	✓
Faxing *	Mono faxing	Mac operating systems supported	✓
Fax transmission speed	3 sec/page	Linux operating systems supported	✓
Modem speed	33.6 Kbit/s	Other operating systems supported	
Features		1 3 7 11	
Recommended duty cycle	2000 - 15000 pages per month	Operational conditions	0000/
Maximum duty cycle * Printing colours *	120000 pages per month Black	Operating relative humidity (H-H) Operating temperature (T-T)	8 - 80% 10 - 32 °C
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PDF	Operating altitude	0 - 5000 m
	1.7, PPDS, PostScript 3		
Input & output capacity			
Total number of input trays *	2		

Input & output capacity		Certificates	
Total input capacity * Total output capacity * Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size * Paper tray media types * ISO A-series sizes (A0A9) *	350 sheets 150 sheets 5 2000 sheets 150 sheets A4 Card stock, Envelopes, Labels, Plain paper, Transparencies A4, A5, A6	Certification	ENERGY STAR, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DOC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DOC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER
Non-ISO print media sizes	Executive, Folio, Legal, Letter,	Sustainability	
JIS B-series sizes (B0B9)	Oficio, Statement, Universal B5	Sustainability certificates	ENERGY STAR
Envelopes sizes	7 3/4, 9, 10, DL	Weight & dimensions	
Paper tray media weight	60 - 120 g/m²	Width	489 mm
Ports & interfaces		Depth	429.5 mm
Standard interfaces	Ethernet, USB 2.0	Height Weight	477 mm 20.6 kg
Direct printing *	✓	Packaging data	2010 119
USB port	✓	Package width	511 mm
USB connector USB 2.0 ports quantity	USB Type-A / USB Type-B 3	Package depth	576 mm
Optional connectivity	Wireless LAN	Package height	614 mm
Network		Package weight	23.9 kg
Ethernet LAN *	✓	Packaging content	
Cabling technology	10/100/1000Base-T(X)	Cartridge(s) included	/
Ethernet LAN data rates	10,100,1000 Mbit/s	Included cartridge capacity (black)	6000 pages ✓
Security algorithms	IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, SSL/TLS, TTLS	Imaging unit included Cables included	Phone
Supported network protocols (IPv4)	TCP / IP IPv4, AppleTalk ™, TCP,	Manual	✓
Supported network protocols (IPv6)	UDP TCP / IP IPv6	Power cord included	✓
Supported Hetwork protocols (II vo)	DHCP, APIPA (AutoIP), BOOTP,	Warranty card	✓
Management protocols	RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPS	Other features	
		Safety sheet	✓
Network printing methods	(SSL /TLS), Finger LPR/LPD, Direct IP (Port 9100), Pull Printing, Microsoft Web Services WSD, Secure IP (Port 96xx), FTP, TFTP, Enhanced IP (Port 9400), ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)	Finishing option	×
		Software CD	✓
		Documentation CD	/
Authentication method	802.1x		
Mobile printing technologies	Apple AirPrint		

