Lexmark MX622ade Laser A4 1200 x 1200 DPI 47 ppm

Brand : Lexmark Product code: 36S0907

Product name: MX622ade

Lexmark MX622ade. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying. Scanning: Colour scanning. Faxing: Mono faxing. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey





Printing		Network	
Print technology *	Laser	Mobile printing technologies	Apple AirPrint
Printing *	Mono printing	Performance	
Duplex printing *	✓	Maximum internal memory	2048 MB
Maximum resolution *	1200 x 1200 DPI	Card reader integrated	1
Print speed (black, normal quality, A4/US Letter) *	47 ppm	Internal memory *	2048 MB
Duplex print speed (black, normal quality, A4/US Letter)	24 ppm	Built-in processor Processor frequency	√ 1200 MHz
Time to first page (black, normal)	6 s	Processor cores	4
Print margins (top, bottom, right, left)	4 mm	Sound pressure level (printing)	55 dB
		Sound pressure level (duplex printing)	54 dB
Copying		Sound pressure level (copying)	56 dB
Duplex copying *	4	Sound pressure level (scanning)	55 dB
Copying *	Mono copying	Sound power level (standby)	14 dB
Copy speed (black, normal quality, A4)	47 cpm	Design	
Time to first copy (black, normal)	6 s	Product colour *	Black, Grey
Copier resize	25 - 400%	Market positioning *	Business
Scanning		Built-in display *	1
Scanning *	Colour scanning	Display diagonal	17.8 cm (7")
Optical scanning resolution (black)	1200 x 600 ppi	Touchscreen	✓
Optical scanning resolution (colour)	600 x 600 ppi	Control type	Touch
Maximum scan resolution	1200 x 600 DPI	Colour display	1
Maximum scan area	215.9 x 355.6 mm	Power	
Scanner type *	Flatbed & ADF scanner	Power consumption (max)	680 W
Scan technology Scan to	CIS E-mail, FTP, PC, USB	Power consumption (average operating)	670 W
Scan speed (colour)	30 ppm	Power consumption (printing)	670 W
Scan speed (black)	47 ppm	Power consumption (copying)	680 W
Duplex scan speed (colour)	60 ppm	Power consumption (scanning)	23.5 W
Duplex scan speed (black)	94 ppm	Power consumption (ready)	16.5 W
Image formats supported	JPEG, JPG, TIFF	Power consumption (sleep)	2.5 W
Document formats supported	PDF, XPS	Power consumption (off)	0.1 W
Fax		Energy Star Typical Electricity Consumption (TEC)	2.1 kWh/week
Duplex faxing	√	System requirements	
Faxing *	Mono faxing	Windows operating systems	
Fax transmission speed	3 sec/page	supported	✓
Modem speed	33.6 Kbit/s	Mac operating systems supported	✓
Features		Linux operating systems supported	✓
Recommended duty cycle	2000 - 20000 pages per month	Other operating systems supported	✓
Maximum duty cycle *	175000 pages per month		

Features		Operational conditions	
Printing colours *	Black	Operating relative humidity (H-H)	8 - 80%
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PDF	Operating temperature (T-T)	10 - 32 °C
. 3	1.7, PPDS, PostScript 3	Operating altitude	0 - 5000 m
Input & output capacity		Certificates	
Total number of input trays * Total input capacity * Total output capacity * Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling	2 650 sheets 250 sheets ✓ 100 sheets 5 2300 sheets 250 sheets	Certification	ENERGY STAR, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DOC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, Ctick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B,
•	A 4		ECMA-370, TED, GOST-R, SII, TER
Maximum ISO A-series paper size *	A4 Card stock, Envelopes, Labels, Plain	Sustainability	
Paper tray media types *	paper, Transparencies	Sustainability certificates	ENERGY STAR
ISO A-series sizes (A0A9) *	A4, A5, A6	Weight & dimensions	
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Width	489 mm
JIS B-series sizes (B0B9)	B5	Depth	476.5 mm
Envelopes sizes	7 3/4, 9, 10, DL	Height	545 mm
Paper tray media weight	60 - 120 g/m²	Weight	22.3 kg
Ports & interfaces		Packaging data	
Standard interfaces	Ethernet, USB 2.0	Package width	552 mm
Direct printing *	✓	Package depth	605 mm
USB port	1	Package height	682 mm
USB connector	USB Type-A / USB Type-B	Package weight	26.6 kg
USB 2.0 ports quantity	3	Packaging content	
Optional connectivity	Wireless LAN	Cartridge(s) included	✓
Network		Included cartridge capacity (black)	6000 pages
Ethernet LAN *	1	Imaging unit included	√
Cabling technology	10/100/1000Base-T(X)	Cables included	Phone
Ethernet LAN data rates	10,100,1000 Mbit/s	Manual	V
Security algorithms	IPSec, LEAP, MD5, MSCHAPv2, PEAP, SNMPv3, SSL/TLS, TTLS	Power cord included Warranty card	4
Supported network protocols (IPv4)	TCP / IP IPv4, AppleTalk ™, TCP, UDP	Other features	
Supported network protocols (IPv6)	TCP / IP IPv6	Safety sheet	✓
Management protocols	DHCP, APIPA (AutoIP), BOOTP, RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL /TLS), Finger	Finishing option Software CD Documentation CD	*
Network printing methods	LPR/LPD, Direct IP (Port 9100), Pull Printing, Microsoft Web Services WSD, Secure IP (Port 96xx), FTP, TFTP, Enhanced IP (Port 9400), ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)		
Authentication method	802.1x		

