

Canon imageRUNNER 1643i Laser A4 1200 x 1200 DPI 43 ppm Wi-Fi

Tuotemerkki : Canon

Tuoteperhe: imageRUNNER

Tuotekoodi: 3630C006

Tuotteen nimi : 1643i

Canon imageRUNNER 1643i. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Mono-skannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Suurin ISO A-luokan paperikoko: A4. Wi-Fi. Suoratulostus. Tuotteen väri: musta, Harmaa



Printing		Paper handling	
Print technology *	Laser	Paper tray media weight	60 - 120 g/m ²
Printing *	Mono printing	Multi-Purpose Tray media weight	60 - 199 g/m ²
Duplex printing *	✓	Duplex media weight	60 - 120 g/m ²
Maximum resolution *	1200 x 1200 DPI	Ports & interfaces	
Print speed (black, normal quality, A4/US Letter) *	43 ppm	Direct printing *	✓
Warm-up time	14 s	USB port	✓
Warm-up time (from sleep mode)	4 s	USB 2.0 ports quantity	3
Secure printing	✓	Network	
Cover page printing function	✓	Wi-Fi *	✓
Booklet printing function	✓	Ethernet LAN *	✓
Copying		Cabling technology	10/100/1000Base-T(X)
Duplex copying *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Copying *	Mono copying	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Maximum copy resolution *	600 x 600 DPI	Near Field Communication (NFC)	✗
Copy speed (black, normal quality, A4)	43 cpm	Security algorithms	802.1x RADIUS, APOP, IPsec, SMTP-AUTH, SNMPv3
Time to first copy (black, normal)	6.3 s	Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
Maximum number of copies	999 copies	Performance	
Copier resize	25 - 400%	Internal memory *	1000 MB
N-in-1 copy function	✓	Built-in processor	✓
ID-card copy function	✓	Processor cores	2
Scanning		Sound pressure level (printing)	54 dB
Duplex scanning *	✓	Design	
Scanning *	Mono scanning	Product colour *	Black, Grey
Optical scanning resolution *	600 x 600 DPI	Market positioning *	Home & office
Scanner type *	ADF scanner	Built-in display *	✓
Scan to	Cloud, E-mail, FTP, Fax, SMB, USB	Display	LCD
Scan speed (black)	20 inch/min	Display diagonal	12.7 cm (5")
Image formats supported	JPEG, TIFF	Touchscreen	✓
Document formats supported	PDF	Control type	Touch
Scan drivers	TWAIN, WIA	Colour display	✓

Fax		Power	
Faxing *	✗	Power consumption (max)	1420 W
Features		Power consumption (standby)	13.6 W
Digital sender	✓	Power consumption (sleep)	0.7 W
Printing colours *	Black	Power consumption (off)	0.1 W
Page description languages	PCL 5, PCL 6, PostScript 3, UFR II	Energy Star Typical Electricity Consumption (TEC)	1.4 kWh/week
Number of printer fonts	229	AC input voltage	220 - 240 V
Input & output capacity		AC input frequency	50 - 60 Hz
Total input capacity *	650 sheets	System requirements	
Total output capacity *	150 sheets	Windows operating systems supported	Windows 10, Windows 7, Windows 8.1
Multi-Purpose tray	✓	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.9 Mavericks
Multi-Purpose tray input capacity	100 sheets	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Paper input type	Cassette	Operational conditions	
Maximum input capacity	2300 sheets	Operating relative humidity (H-H)	20 - 80%
Paper handling		Storage temperature (T-T)	10 - 30 °C
Maximum ISO A-series paper size *	A4	Sustainability	
Paper tray media types *	Bond paper, Plain paper, Recycled paper, Thick paper, Thin paper	Sustainability certificates	Blue Angel, ENERGY STAR
Multi-purpose tray media types	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Thick paper, Thin paper	Weight & dimensions	
ISO A-series sizes (A0...A9) *	A4, A5, A6	Width	480 mm
ISO B-series sizes (B0...B9)	B5	Depth	595 mm
Non-ISO print media sizes	Executive, Index card, Legal, Letter, Statement	Height	452 mm
Envelopes sizes	10, C5, DL, Monarch	Weight	19 kg
Custom media width	76.2 - 127 mm	Logistics data	
Custom media length	216 - 355.6 mm	Harmonized System (HS) code	84433100



4549292137330

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.