TP-Link TL-MR150 langaton reititin Nopea Ethernet Yksi kaista (2,4 GHz) 4G musta

Tuotemerkki : TP-Link   **Tuotekoodi:** TL-MR150

Tuotteen nimi : TL-MR150

TP-Link TL-MR150. WAN -liitintyyppi: RJ-45. Wi-Fi-taajuus: Yksi kaista (2,4 GHz), Wi-Fi-standardi: Wi-Fi 4 (802.11n), WLAN-tiedonsiirtonopeus (maks.): 300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Nopea Ethernet, Ethernet LAN -datanopeudet: 10,100 Mbit/s, Kaapelitekniikka: 10/100Base-T(X). Mobiiliverkon sukupolvi: 4G, 3G-standardit: DC-HSPA+, HSPA, HSPA+, UMTS, 4G-standardit: LTE-TDD & LTE-FDD. Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK

WAN connection

Ethernet WAN *	✔
DSL WAN *	✔
SIM card slot *	✔
3G/4G USB modem compatibility *	✔
WAN connection type	RJ-45

Wireless LAN features

Wi-Fi band *	Single-band (2.4 GHz)
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)
WLAN data transfer rate (max) *	300 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Network

Ethernet LAN *	✔
Ethernet LAN interface type *	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Dynamic DNS (DDNS)	✔
VPN Passthrough	✔
VPN support	PPTP, L2TP, IPSec
Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n)	20 dBmW
Receiver sensitivity	11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm

Mobile network

Mobile network generation	4G
3G	✔

Security

Stateful Packet Inspection (SPI)	✔
DoS attack prevention	✔
MAC address filtering	✔
IP address filtering	✔
DMZ support	✔

Protocols

DHCP client	✔
DHCP server	✔
Universal Plug and Play (UPnP)	✔
Supported network protocols	IPv4, IPv6

Design

Product colour	Black
On/off switch	✔
Product type *	Tabletop router

Certificates

Certification	CE, RoHS

Packaging content

Cables included	LAN (RJ-45)
AC adapter included	✔
Quick installation guide	✔

Antenna

Antenna design *	External
Antenna connector type	N-type
Antennas quantity	2

Mobile network		**Power**	
4G	✔	Power source type *	DC
3G standards	DC-HSPA+, HSPA, HSPA+, UMTS	Output voltage	9 V
4G standard	LTE-TDD & LTE-FDD	Output current	0.85 A
UMTS bands supported	900,2100 MHz	**Operational conditions**	
4G bands supported	800,900,1800,1900,2100,2300,2500,2600 MHz	Operating temperature (T-T)	0 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN (RJ-45) ports *	4	Operating relative humidity (H-H)	10 - 90%
USB port *	✘	Storage relative humidity (H-H)	5 - 90%
Memory card slot(s)	✘	**System requirements**	
DC-in jack	✔	Browser supported	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Management features		Windows operating systems supported	Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Quality of Service (QoS) support	✔		
Reset button	✔	Linux operating systems supported	✔
WPS push button	✔	Mac operating systems supported	✔
Security		**Weight & dimensions**	
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Width	202 mm
Firewall	✔	Depth	141 mm
Guest access	✔	Height	33.6 mm
Access Control List (ACL)	✔	**Packaging data**	
		Package type	Box

6935364089672