Samsung 50" Crystal UHD 4K Signage QE50T

Brand : Samsung

Product family: QET

Product code: LH50QETELGCXEN

Product name : 50" Crystal UHD 4K Signage QE50T

- Upscale your business

- Incredible UHD picture quality

- Crisp and vivid color expression

50", LED, 4K UHD (3840 x 2160), 300 nit, 4000:1, 89/89, 8 ms, RJ-45, HDCP, HDMI, RS232, AC 100-240V, 50/60Hz, 1116.8 x 644.2 x 59.9 mm, 11.7 kg

Samsung 50" Crystal UHD 4K Signage QE50T. Product design: Digital signage flat panel. Display diagonal: 127 cm (50"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 300 cd/m², HD type: 4K Ultra HD. Operating system installed: Tizen 4.0. Product colour: Black





Display		Design	
LED backlight	1	Panel mounting interface	200 x 200 mm
Display diagonal *	127 cm (50")	Bezel colour	Black
-1	LED	Performance	
Display resolution *	3840 x 2160 pixels	Purpose *	Universal
Display brightness * HD type *	300 cd/m² 4K Ultra HD	HDCP	v
Touchscreen *		HDCP version	2.2
Response time	× 8 ms	Power	
Contrast ratio (typical)	4000:1	Power consumption (typical) *	149 W
Dynamic contrast ratio marketing	Mega DCR	Power consumption (sleep)	0.5 W
name	5	Energy efficiency class (SDR)	G
Viewing angle, horizontal Viewing angle, vertical	89° 89°	Energy consumption (SDR) per 1000 hours	95 kWh
Pixel pitch	0.285375 x 0.285375 mm	AC input voltage	100 - 240 V
Display diagonal (metric)	125 cm	AC input frequency	50/60 Hz
Horizontal scan range	15 - 135 kHz	Energy efficiency scale	A to G
Vertical scan range	24 - 75 Hz	Computer system	
Haze rate	2%	Operating system installed	Tizen 4.0
Pixel frequency (max) Colour gamut	594 MHz 72%	Weight & dimensions	
Ports & interfaces		Display width	1116.8 mm
HDMI ports quantity *	2	Display depth	59.9 mm
HDMI version	2.0	Display height	644.2 mm
HDMI input ports quantity	2	Display weight	11.7 kg
DVI port *	×	Packaging data	
USB port *	1	Package width	1264 mm
USB ports quantity	1	Package depth	150 mm
Ethernet LAN *	1	Package height	780 mm
Wi-Fi *	×	Package weight	16.1 kg
Audio (L/R) out	1	Operational conditions	
RS-232 interface	√	Operating temperature (T-T)	0 - 40 °C
Design		Operating relative humidity (H-H)	10 - 80%
Product design *	Digital signage flat panel	Certificates	
Placement supported *	Indoor	Certification	Class B 60950-1

Design		Other features	
Product colour *	Black	Flash memory	8000 MB
Screen shape	Flat	Optional features	WMN4070SE STN-L4355F
VESA mounting *	1		



8806090505188

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.