

C-KVM KVM Cable

| C-KVM



Kramer's C-KVM cable is an all-in-one design of video & control cables for the Secure KVM switchers. It makes connections and setups neatly and easily, while providing image clarity for high-resolution applications

FEATURES

Quality Construction - Constructed high quality conductors and shielding in a PVC jacket, terminated with male connectors

Connectors - Molded DVI, VGA, USB - gold/nickel plated

Molded Strain Relief

Easy Installation - 300 mm - 500 mm long spread at the USB end to fit large switchers RoHS Compliant

Varied Selection of Connector Configurations - Available in version of DVI-D Single-Link and USB (A-B), DVI-D Dual-Link and USB (A-B), VGA to DVI-A and USB (A-B)



TECHNICAL SPECIFICATIONS

PHYSICAL Conductors: 30AWG(7/01), 28AWG(7/0.127)

Overall Sheath Diameter: 6mm/3.5mm (C-KVM/1-6), 8mm/3.5mm (C-KVM/2-6,

C-KVM/3-6)

Outer Sheath Color: Black

Length: 6ft (1.8m)

Terminations: C-KVM/1-6: End 1: 1 single-link DVI-D (M) + USB-A (M); End 2: 1 single-link

DVI-D(M) + 1 USB-B(M),

C-KVM/2-6: End 1: 1 dual-link DVI-D (M) + USB-A (M); End 2: 1 VGA (HD-15)

(M) + 1 USB-A (M),

C-KVM/3-6: End 1: 1 VGA (HD-15) (M) + USB-A (M); End 2: 1 DVI-A (M) + 1

USB-B (M)

Shielding: Aluminum-Mylar foil with braid

REGULATORY Standards: 2011/65/ EU



CONFIGURATIONS

C-KVM/1-6	KVM Cable DVI-D Single-Link and USB (A-B)
C-KVM/2-6	KVM Cable DVI-D Dual-Link and USB (A-B)
C-KVM/3-6	KVM Cable VGA to DVI-A and USB (A-B)