## StarTech.com DK30C2DAGPD kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : StarTech.com

Tuotekoodi: DK30C2DAGPD



StarTech.com DK30C2DAGPD. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery asti: 100 W. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Tuotteen väri: musta, Tiedonsiirtonopeus: 5 Gbit/s, Digitaalinen enimmäistarkkuus: 4096 x 2160 pikseliä. Virtalähteen malli: USB, Virtalähde: 100 W, Virrankulutus: 15 W. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...





ports quantityIWindows 10 Home, Windows 10USB Power Delivery (USB PD)USB Power Delivery revision3.0USB Power Delivery up to100 WDisplayPorts quantity2Microphone in *×NetworkEthernet LAN *Ethernet LAN (RJ-45) ports1Ethernet LAN (RJ-45) ports1IEthernet LAN (RJ-45) ports1Ethernet LAN data rates10,100,1000 Mbit/sNetworking standardsIEEE 802.3, IEEE 802.3ab, IEEE 802.3uAuto MDI/MDI-XFull duplexFull duplexVerySupportNetworkStatter, Windows 8.1 Pro, Windows 8.1Professional solutions 8.1Professional solutions 8.1Providows 8.1P	Ports & interfaces		Power	
SortwareUSB 2.0 ports quantity *1USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity11USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity1USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity1USB 2.0 ports quantity1USB Power Delivery (USB PD)V.USB Power Delivery (USB PD).USB Power Delivery revision3.0USB Power Delivery up to100 WDisplayPorts quantity2Microphone in *XNetwork.Ethernet LAN *.Ethernet LAN *.Fuil duplex<	Connectivity technology *	Wired	Power consumption (typical)	15 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity*1Windows 10 Education x64, Windows 10 Education x64, Windows 10 Education x64, Windows 10 Home, Windows 10 Education x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Home, Windows 7 Home, Basic, K64, Windows 7 Home, Premium, K64, Windows 8 Home, Premium, K64, Windows 8 Home			Software	
NetworkSupportedWindows 7 Professional, Windows 7 Professional, K4, Windows 7 Starter, Windows 7 Starter, X64, Windows 7 Starter, Windows 7 Ultimate, Windows 7 Starter, Windows 7 Ultimate, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 7 Ultimate X64, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, K64, Windows 8 Enterprise, K64, Windows 8 S Y02.3uAuto MDI/MDI-XFull duplexYOperating temperature (T-T)0 - 50 °CYStorage temperature (T-T)0 - 50 °CData transfer rateS Gbit/sOperating temperature (T-T)0 - 50 °CData transfer rateS Gbit/sOperating relative humidity (H-H)0 - 95%Waximum digital resolution4096 x 2160 pixelsWeight & dimensionsVASP supportIWidth60 mm	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity USB Power Delivery (USB PD) USB Power Delivery revision USB Power Delivery up to DisplayPorts quantity	1 1 ✓ 3.0 100 W 2		Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium,
Etherner LAN*✓Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate X64, Windows 7 Ultimate, Windows 7 Ultimate X64, Windows 7 X64, Windows 8 Vindows 8 Enterprise, Windows 8 I. Enterprise, windows 8.1 Enterprise, 	Network		supported	Windows 7 Professional, Windows 7
Ethernet LAN (RJ-45) ports1Windows 7 Ultimate, Windows 7Ethernet LAN data rates10,100,1000 Mbit/sUltimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8.1, Windows 8.1, Enterprise, Windows 8.1, Windows 8.1, Enterprise, Windows 8.1, Enterprise, Windows 8.1, Enterprise, Windows 8.1, Enterprise, Windows 8.1, Windows 8.1, Enterprise, Windows 8.1, Enterpri	Ethernet LAN *	✓		
Litterinet Exit data faces10,100,1000 minusWindowsWindows 8, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 8 Pro, Windows 8 Enterprise, X64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1, Windows 8.	Ethernet LAN (RJ-45) ports	1		Windows 7 Ultimate, Windows 7
Auto MDI/MDI-X </td <td></td> <td>IEEE 802.3, IEEE 802.3ab, IEEE</td> <td rowspan="4"></td> <td rowspan="4">Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1</td>		IEEE 802.3, IEEE 802.3ab, IEEE		Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1
Full duplex✓Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro, X64, Windows 8.1 Pro, Windows 8.1 Pro, X64, Windows 8.1 X64PerformanceOperational conditionsCard reader integrated *XOperating temperature (T-T)0 - 50 °CData transfer rate5 Gbit/sStorage temperature (T-T)-20 - 70 °CMaximum digital resolution4096 x 2160 pixelsOperating relative humidity (H-H)0 - 95%Product colour *BlackWeight & dimensionsWidthUASP support✓Width60 mm	Auto MDI/MDI-X			
NoG support Xo4, Windows 8.1 PPo, PPO, PPO, PPO, PPO, PPO, PPO, PPO,		-		
Card reader integrated *×Operating temperature (T-T)0 - 50 °CData transfer rate5 Gbit/sStorage temperature (T-T)-20 - 70 °CMaximum digital resolution4096 x 2160 pixelsOperating relative humidity (H-H)0 - 95%Product colour *BlackWeight & dimensionsUASP support✓Width60 mm		-		
Call reade integrated integr	Performance		Operational conditions	
Product colour * Black Weight & dimensions   UASP support ✓ Width 60 mm	Data transfer rate	ata transfer rate 5 Gbit/s	Storage temperature (T-T)	-20 - 70 °C
Width Oblinit	5	1	Weight & dimensions	
Housing material Plastic Depth 120 mm	UASP support	✓	Width	60 mm
	Housing material	Plastic	Depth	120 mm

Publication date: 18-DEC-2024. Prints or copies of Information are only valid on the printed Publication date

Performance		Weight & dimensions	
Brand compatibility Certification	Any brand CE, FCC, REACH	Height Weight	18.8 mm 150 g
Power		Packaging data	
Power source type Power supply	USB 100 W	Package width Package depth Package height Package weight	145 mm 208 mm 42 mm 300 g
		Packaging content	
		Cables included	USB Type-C
		Quick start guide	1
		Technical details	
		Compliance certificates	RoHS
		Logistics data	
		Products per master (outer) case Master (outer) case width Master (outer) case length Master (outer) case height Harmonized System (HS) code	24 pc(s) 310 mm 450 mm 280 mm 84733020
		Other features	
		Chipset	VIA/VLI - VL102, VIA/VLI - VL170, VIA/VLI - VL817, MegaChips - STDP4320, RealTek - RTL8153





065030878746

0065030878746

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.