ASUS J1900I-C Mini ITX

Tuotemerkki : ASUS Tuotekoodi: 90MB0JH0-M0EAYM

Tuotteen nimi: J1900I-C

ASUS J1900I-C. Suoritinvalmistaja: Intel, Yhteensopivat prosessorit: Intel® Celeron®, Prosessorimalli: J1900. Sisäinen enimmäismuisti: 8 GB, Muistipaikkojen tyyppi: SO-DIMM, Muistikanavat: Kaksikanava. Tuetut tallennusasemaliitännät: SATA, Tuetut tallennusasematyypit: SSD. Näytönohjainperhe: Intel, Enimmäiserottelutarkkuus: 2560 x 1600 pikseliä, Sisältyvän näytönohjaimen malli: Intel® HD Graphics. Ethernet-liitännän tyyppi: Gigabitti Ethernet, LAN-kontrolleri: Realtek RTL8111G





Processor		Internal I/O	
Processor manufacturer * Compatible processor series *	Intel Intel® Celeron®	TPM connector 12V power connector	*
Processor model Processor cores	J1900 4	Rear panel I/O ports	•
Memory Number of memory slots * 2 Memory slots type SO-DIMM Memory channels Dual-channel ECC compatibility Non-ECC	SO-DIMM Dual-channel	USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports * PS/2 ports quantity HDMI ports quantity *	4 1 1 1
Supported memory clock speeds Maximum internal memory *	1333 MHz 8 GB	COM ports quantity Network	1
Storage controllers Supported storage drive types Supported storage drive interfaces	SSD SATA	Ethernet LAN Ethernet interface type LAN controller	✓ Gigabit Ethernet Realtek RTL8111G
Graphics		Features	Nowher Williams
Parallel processing technology support * On-board graphics card Graphics card family Intel Maximum resolution 2560 x 1600 pixels	Audio output channels * Motherboard form factor * Motherboard chipset family * Windows operating systems supported	8 channels mini ITX Intel Windows 7, Windows 8, Windows 8.1	
DirectX version On-board graphics card model	11 Intel® HD Graphics	Expansion slots	
Internal I/O	inicia fib diapnics	PCI Express x1 (Gen 2.x) slots Mini PCI Express slots	1 1
USB 2.0 connectors * Number of SATA II connectors Front panel audio connector Number of EATX power connectors	1 2 •• 1	BIOS BIOS type * BIOS memory size ACPI version	UEFI AMI 64 Mbit 2.0a

Internal I/O		BIOS	
CPU fan connector	√ s 1	Desktop Management Interface (DMI) version	2.0
Number of chassis fan connectors			
Number of COM connectors	1	Logistics data	
		Harmonized System (HS) code	84733020
		Weight & dimensions	
		Width	170 mm
		Depth	170 mm



4716659734703

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.