


## ASUS MB Pro WS C621-64L SAGE/10 G Intel® C621 LGA 3647 (Socket P) CEB

**Tuotemerkki :** ASUS

**Tuotekoodi:** 90SW00S0-M0EAY0

**Tuotteen nimi :** MB Pro WS C621-64L SAGE/10 G

ASUS MB Pro WS C621-64L SAGE/10 G. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 3647 (Socket P), Yhteensopivat prosessorit: Intel® Xeon®, Intel® Xeon W. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 1,54 TB, Muistikanavat: Hexa-kanava. Tuetut tallennusasemaliitännät: SATA III. Ethernet-liitännän tyyppi: 10 Gigabit Ethernet, LAN-kontrolleri: Intel® X550-AT2. Komponentti (tuotteelle): Työasema, Emolevyn muototekijä: CEB, Emolevyn piirisarja: Intel® C621



<b>Processor</b>		<b>Rear panel I/O ports</b>	
Processor manufacturer *	Intel	Headphone outputs	1
Processor socket *	LGA 3647 (Socket P)	Microphone in	✓
Compatible processor series *	Intel® Xeon®, Intel Xeon W	<b>Network</b>	
Processor number of cores supported	28	Ethernet LAN	✓
<b>Memory</b>		Ethernet interface type	10 Gigabit Ethernet
Supported memory types *	DDR4-SDRAM	LAN controller	Intel® X550-AT2
Memory channels	Hexa-channel	<b>Features</b>	
Supported memory clock speeds	2666,2933 MHz	Motherboard chipset *	Intel® C621
Maximum internal memory *	1.54 TB	Audio output channels *	7.1 channels
<b>Storage controllers</b>		Component for *	Workstation
Supported storage drive interfaces *	SATA III	Motherboard form factor *	CEB
<b>Internal I/O</b>		<b>Expansion slots</b>	
USB 2.0 connectors *	1	PCI Express x16 (Gen 3.x) slots	4
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Number of M.2 (M) slots	1
Number of SATA III connectors *	10	<b>BIOS</b>	
ATX Power connector (24-pin)	✓	BIOS type *	UEFI AMI
Power fan connector	✓	<b>Logistics data</b>	
CPU fan connector	✓	Harmonized System (HS) code	84733020
TPM connector	✓	<b>Weight &amp; dimensions</b>	
<b>Rear panel I/O ports</b>		Width	305 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Depth	277 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1	<b>Other features</b>	
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1	PCI Express x4 (Gen 3.x) slots	1
		Supported DIMM module capacities	16GB, 32GB, 64GB, 128GB
		Supported LRDIMM clock speeds	2666,2933 MHz

**Rear panel I/O ports**

Ethernet LAN (RJ-45) ports \* 2

**Other features**

Supported RDIMM clock speeds 2666,2933 MHz

Number of DIMM slots 12

Number of processors supported 1



4718017391115

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date