

ASUS TUF-GAMING-650B power supply unit 650 W 20+4 pin ATX ATX Black

Brand : ASUS

Product code: 90YE00D1-B0NA00

Product name : TUF-GAMING-650B

- Capacitors and chokes pass demanding tests to achieve Military-grade Certification
 - Dual ball fan bearings can last up to twice as long as sleeve bearing designs
 - A protective PCB coating protects against moisture, dust, and extreme temperatures
 - An 80 Plus Bronze Certification is earned with high-quality components that pass rigorous testing
 - Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
 - 0dB technology lets you enjoy light gaming in relative silence
 - Sleeved cables leave your rig looking tactically clean
 - 80cm 8-pin CPU connector (EPS 12V)
- ATX12V, 650W, 100 - 240 V, 25A, 80Plus Bronze



Power		Ports & interfaces	
Total power *	650 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	80 cm
Input current	25 A	Cabling type	Non-Modular
Combined power (+3.3V)	130 W	Performance	
Combined power (+12V)	612 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+5V)	130 W	Purpose *	PC
Combined power (-12V)	9.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	15 W	Design	
Max output current (+3.3V)	25 A	Product colour	Black
Max output current (+12V)	51 A	Cooling type	Active
Max output current (+5V)	25 A	Fan diameter	13.5 cm
Max output current (-12V)	0.8 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	On/off switch	✓
Ports & interfaces		Packaging content	
Motherboard power connector *	20+4 pin ATX	Cables included	CPU, PCIe, Peripheral (Molex), SATA
Motherboard power cable length	60 cm	Weight & dimensions	
Number of SATA power connectors	5	Width	150 mm
SATA power cable length	400 mm	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	4	Height	86 mm
PCI Express power connectors (6+2 pin)	4	Weight	2.06 kg
PCI Express power cable length	60 cm	Packaging data	
		Package weight	2.75 kg
		Package type	Box
		Technical details	
		Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code 84733020



4718017724272



4718017724159

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-NOV-2024. Prints or copies of Information are only valid on the printed Publication date