QNAP TS-1273AU-RP-8G NAS- ja tallennuspalvelimet Teline (2U) Ryzen Embedded V1500B 8 GB DDR4 0 TB QNAP QTS Alumiini, musta

Tuotemerkki : QNAP

Tuotekoodi: TS-1273AU-RP-8G

Tuotteen nimi : TS-1273AU-RP-8G

QNAP TS-1273AU-RP-8G. Malli: NAS. Alustatyyppi: Teline (2U). Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Ryzen Embedded, Prosessorimalli: V1500B, Prosessorin taajuus: 2,2 GHz. Sisäinen muisti: 8 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QNAP QTS






Storage		Design	
Storage drive capacity * Storage drive interface *	0 GB Serial ATA II, Serial ATA III	Chassis type * Cooling type *	Rack (2U) Active
Supported storage drive interfaces		Product colour	Aluminium, Black
Storage drive size	2.5/3.5"	Number of fans	2 fan(s)
Storage drive sizes supported	2.5,3.5"	Fan diameter	8 cm
RAID support *	1	Fan diameter 2	8 cm
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Performance	
Online RAID migration	1	Type *	NAS
Online RAID expansion	1	Device class *	Small & Medium Business
RAID rebuild	1	Backup function *	1
Hot-swap drive bays	1	Backup features	Cloud, iSCSI LUN
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Buzzer	 Image: A set of the set of the
Storage drives installed *	×	Multilingual support	 Image: A set of the set of the
Total installed storage capacity st	0 ТВ	Snapshot	1
Number of storage drives supported *	12	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSL/TLS
Installed storage drive type *	×	Access Control List (ACL)	1
Supported storage drive types $*$	HDD & SSD	Reset button	 Image: A set of the set of the
Bad block scan	1	On/off switch	1
Disk roaming	1	Built-in FTP server	1
Processor	AMD	Browser supported	Apple Safari 7+, Google Chrome, Mozilla Firefox
Processor manufacturer * Processor generation	AMD AMD Ryzen Embedded V1000 Series	System log	 Image: A set of the set of the
Processor family *	Ryzen Embedded	Hot spare	1
Processor model *	V1500B	Disk scan	1
Processor frequency *	2.2 GHz	S.M.A.R.T. support	1
Processor cores	4	Share folder	CIFS/SMB
Processor threads	8	Universal Plug and Play (UPnP)	v
L2 cache	2 MB	USB copy function	1
L3 cache	4 MB	Software	
Memory			01110.072
Internal memory *	8 GB	Operating system installed *	QNAP QTS
Internal memory type	DDR4	Operating system version Windows operating systems	5.0.0
Maximum RAM supported	32 GB	supported	Windows 10, Windows 7, Windows 8

Memory		Software	
Memory slots	2	Linux operating systems supported	1
Memory form factor Flash memory	DIMM 5000 MB		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3
Network		Mac operating systems supported	
Ethernet LAN * Ethernet LAN data rates DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system Dynamic DNS (DDNS)	 100,1000,2500 Mbit/s . .<td>Server operating systems supported Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units</td><td>Catalina Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2012, Windows Server 2012 R2, Windows Server 2012 R2 x64, Windows Server 2012 x64, Windows Server 2016, Windows Server 2016 x64, Windows Server 2019</td>	Server operating systems supported Other operating systems supported Power Power supply location Power supply unit (PSU) capacity Number of power supply units	Catalina Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2012, Windows Server 2012 R2, Windows Server 2012 R2 x64, Windows Server 2012 x64, Windows Server 2016, Windows Server 2016 x64, Windows Server 2019
WLAN adapter supported	<	Power consumption (typical)	78.92 W
Ports & interfaces		Power consumption (sleep)	43.67 W
USB port *	✓	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Weight & dimensions	
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1	Width * Depth *	482 mm 425 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Height *	89 mm
Ethernet LAN (RJ-45) ports *	2	Weight Package weight	9.69 kg 14.6 kg
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

Storage temperature (T-T)	-20 - 70 °C
Logistics data	

Harmonized System (HS) code 84714100



4713213517901

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.