

DELL UltraSharp U2421E LED display 61,2 cm (24.1") 1920 x 1200 pikseliä WUXGA LCD Hopea

Tuotemerkki : DELL

Tuoteperhe: UltraSharp

Tuotekoodi: DELL-U2421E

Tuotteen nimi : U2421E

DELL UltraSharp U2421E. Näytön halkaisija: 61,2 cm (24.1"), Näytön erottelutarkkuus: 1920 x 1200 pikseliä, HD-tyyppi: WUXGA, Näytön teknologia: LCD, Vasteaika (tyypillinen): 8 ms, Vakiokuvasuhde: 16:10, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: Hopea






Display		Ergonomics	
Display diagonal *	61.2 cm (24.1")	Pivot	1
Display resolution *	1920 x 1200 pixels	Pivot angle	-90 - 90°
HD type *	WUXGA	Swivelling	1
Native aspect ratio *	16:10	Swivel angle range	-45 - 45°
Display technology *	LCD	Tilt adjustment	
Panel type *	IPS	Tilt angle range	-5 - 21°
Backlight type	LED	5 5	-9 - 21
Touchscreen *	×	Power	
Display brightness (typical)	350 cd/m ²	Energy efficiency class (SDR) *	E
Response time *	8 ms	Energy efficiency class (HDR) *	Not available
Screen shape *	Flat	Energy consumption (SDR) per 1000 hours *	17 kWh
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Power consumption (typical) *	17.2 W
		Power consumption (standby) *	0.2 W
		Power consumption (max)	186 W
	480i, 480p, 576i, 576p, 720p, 1080i,	Power consumption (off)	0.2 W
		Power consumption (PowerSave)	16.1 W
Contrast ratio (typical) *	1000:1	AC input voltage	100 - 240 V
Maximum refresh rate *	60 Hz	AC input frequency	50 - 60 Hz
Viewing angle, horizontal	178°	Power supply type	Internal
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours *	16.78 million colours	European Product Registry for	344899
Response time (fast)	5 ms	Energy Labelling (EPREL) code	
Pixel pitch	0.27 x 0.27 mm	Operational conditions	
Pixel density	93.95 ppi	Operating temperature (T-T)	0 - 40 °C
Horizontal scan range	30 - 83 kHz	Storage temperature (T-T)	-20 - 60 °C
Vertical scan range	49 - 76 Hz	Operating relative humidity (H-H)	10 - 80%
Viewable size, horizontal	51.8 cm	Storage relative humidity (H-H)	5 - 90%
Viewable size, vertical	32.4 cm		

Display		Weight & dimensions	
Viewable size diagonal High Dynamic Range (HDR) supported Colour gamut Performance	61.1 cm × 99%	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand)	530.8 mm 173 mm 510.7 mm 5.7 kg 530.8 mm
NVIDIA G-SYNC *	×	Depth (without stand) Height (without stand)	50 mm 339.3 mm
AMD FreeSync *	×	Weight (without stand)	4 kg
Multimedia		Bezel width (side)	6.2 mm
Built-in speaker(s) *	×	Bezel width (top)	6.2 mm
Built-in camera *	×	Bezel width (bottom)	9.1 mm
Design		Packaging data	
Market positioning * Product colour * Front bezel colour Detachable stand	Business Silver Black	Package width Package depth Package height Package weight	723.1 mm 139.9 mm 427 mm 8.6 kg
Feet colour	Silver	Sustainability	
Ports & interfaces		Sustainability certificates	ENERGY STAR
Built-in USB hub *	1	Carbon footprint	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Total carbon footprint (kg of CO2e)	610
USB upstream port type Number of upstream ports	USB Type-C 1	Total carbon emissions, standard deviation (kg of CO2e)	106
USB Type-A downstream ports quantity	3	Carbon emissions, manufacturing (kg of CO2e)	434
USB Type-C downstream ports quantity	1	Carbon emissions, logistics (kg of CO2e)	45
DVI port	×	Carbon emissions, energy usage (kg of CO2e)	128
HDMI * HDMI ports quantity	✓ 1	Carbon emissions, end-of-life (kg of CO2e)	3
HDMI version DisplayPorts quantity	1.4 2	Total carbon emissions, w/o use phase (kg of CO2e)	482
DisplayPort version	1.4	Other features	
Audio input	×	Ethernet LAN data rates	10,100,1000 Mbit/s
Audio output	 Image: A second s	Ethernet LAN (RJ-45) ports	1
Headphone out *	1	Logistics data	
Headphone outputs	1	Harmonized System (HS) code	85285210
Headphone connectivity	3.5 mm		
Network			
Wi-Fi	×		

Ergonomics

VESA mounting *	✓
Panel mounting interface	100 x 100 mm
Cable lock slot *	✓
Height adjustment *	✓
Height adjustment	15 cm









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.