



## APC BX1200MI-GR UPS-virtalähde Linjainteraktiivinen 1,2 kVA 650 W 4 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** BX1200MI-GR

**Tuotteen nimi :** BX1200MI-GR

APC BX1200MI-GR. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,2 kVA, Lähtöteho: 650 W. Pistorasian tyypit: Tyyppi F, Virtapistoke: Tyyppi F, Ulostulojen määrä: 4 AC-pistorasia(a).

Akkuteknologia: Sealed Lead Acid (VRLA), Tyypillinen varmuuskopioaika täydellä kuormituksella: 1 min, Tyypillinen varmuuskopioaika puolikkaalla kuormituksella: 5 min. Kotelo: Kompakti, Tuotteen väri: musta, Johdon pituus: 1,2 m. Tuotteen leveys: 140 mm, Tuotteen syvyys: 390 mm, Tuotteen korkeus: 190 mm



### Features

UPS topology *	Line-Interactive
Output power capacity *	1.2 kVA
Output power *	650 W
Waveform *	Sine
Input operation voltage (min) *	140 V
Input operation voltage (max) *	300 V
Input frequency *	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Output frequency regulation	0.5 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	✓
Surge energy rating	273 J
Response time	6 ms
Input power factor	0.54
Noise level	40 dB
Surge protection	✓
Audible alarm(s)	✓
Audible alarm modes	Low battery alarm

### Ports & interfaces

AC outlet types	Type F
Power plug	Type F
AC outlets quantity	4 AC outlet(s)
USB port	✓
USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2

### Battery

Typical backup time at full load	1 min
Typical backup time at half load	5 min
Battery life (max)	2 year(s)
Battery recharge time	8 h

### Design

Form factor *	Compact
Cable length	1.2 m
Product colour *	Black
LED indicators	✓
International Protection (IP) code	IP20
Certification	CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2

### Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m


### Technical details

Compliance certificates	RoHS
-------------------------	------

### Weight & dimensions

Width	140 mm
Depth	390 mm
Height	190 mm
Weight	7.6 kg
Package width	235 mm
Package depth	495 mm
Package height	297 mm

<b>Battery</b>		<b>Weight &amp; dimensions</b>	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	8.6 kg
		<b>Packaging data</b>	
		Cables included	Input power cable
		Manual	✓
		<b>Logistics data</b>	
		Harmonized System (HS) code	85078000



0731304410867



731304410867

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.