



APC SRT3000RMLW-IEC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2700 W 8 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SRT3000RMLW-IEC

Tuotteen nimi : SRT3000RMLW-IEC

APC SRT3000RMLW-IEC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 505 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	3 kVA	Rack capacity	2U
Output power *	2700 W	Cable length	2.44 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	100 V	Display type	LCD
Input operation voltage (max) *	275 V	LED indicators	✓
Input frequency *	40/70 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Output frequency regulation	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	340 J	Storage relative humidity (H-H)	0 - 95%
Efficiency	93.5%	Operating altitude	0 - 3000 m
Crest factor	3:1	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO)	✓	Certificates	
Noise level	55 dB	Compliance certificates	RoHS
Surge protection	✓	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Audible alarm(s)	✓	Packaging content	
Web-based management	✓	Rack mount kit	✓
Auto-restart	✓	Cables included	USB cable
Ports & interfaces		Quick installation guide	✓
AC outlet types	C13 coupler, C19 coupler	Sustainability	
Power plug	C20 coupler	Sustainability certificates	ENERGY STAR
AC outlets quantity	8 AC outlet(s)	Weight & dimensions	
Number of output IEC jumpers	2	Width	432 mm
USB port	✓	Depth	635 mm
Serial interface	✓	Height	85 mm
Serial interface type	RJ-45	Weight	31.3 kg
SmartSlot	✓	Packaging data	
Battery		Bracket	✓
Battery technology	Sealed Lead Acid (VRLA)	Warranty card	✓
Battery capacity	505 VAh	Software CD	✓
Number of batteries supported	1	Package width	599 mm
Typical backup time at full load	4 min	Package depth	871 mm
Typical backup time at half load	11.8 min	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	39.9 kg
Battery recharge time	3 h	Logistics data	
Hot-swap battery	✓	Products per pallet	6 pc(s)
Automatic battery test	✓		
Cold start	✓		

Logistics data


Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	4983.65

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V



0731304320074



731304320074

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-MAR-2025. Prints or copies of Information are only valid on the printed Publication date