



APC Easy UPS ONLINE SRV RM Ext. 3000VA230V UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2400 W 7 AC- pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SRV3KRILRK

Tuotteen nimi : Easy UPS ONLINE SRV RM Ext.
3000VA230V

APC Easy UPS ONLINE SRV RM Ext. 3000VA230V. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2400 W. Pistorasian tyypit: C13 liitin, C19 liitin, Ulostulojen määrä: 7 AC-pistorasia(a), USB-portin tyyppi: USB B-tyyppi. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 72 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 4U. Tuotteen leveys: 86 mm, Tuotteen syvyys: 438 mm, Tuotteen korkeus: 432 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Battery recharge time	5.5 h
Output power capacity *	3 kVA	Charging current	4 A
Output power *	2400 W	Design	
Waveform *	Pure sine	Form factor *	Rackmount
Input operation voltage (min) *	110 V	Rack capacity	4U
Input operation voltage (max) *	285 V	Cable length	1.5 m
Input frequency *	40/70 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	International Protection (IP) code	IP20
Output frequency	50/60 Hz	Operational conditions	
Output voltage regulation	3%	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	600 J	Storage temperature (T-T)	-20 - 50 °C
Efficiency	88%	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Noise level	50 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Power source type	AC	Weight & dimensions	
Detachable power cord	✓	Width	86 mm
Ports & interfaces		Depth	438 mm
AC outlet types	C13 coupler, C19 coupler	Height	432 mm
AC outlets quantity	7 AC outlet(s)	Weight	9.5 kg
USB port	✓	Package width	554 mm
USB port type	USB Type-B	Package depth	240 mm
Serial interface	✓	Package height	700 mm
RS-232 ports	1	Package weight	1.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
Battery voltage	72 V	Cables included	Input power cable, Output power cable, RS-232, USB cable
Battery life (max)	5 year(s)	Manual	✓
		Logistics data	
		Harmonized System (HS) code	85078000



0731304405221



731304405221



8592978285210

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.