



## APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT1000RMXLI-NC

Product name : Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit



Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit


APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit. UPS topology: Double-conversion (Online), Output power capacity: 1 kVA, Output power: 1000 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 48 V, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Cable length: 1.5 m. Width: 432 mm, Depth: 505 mm, Height: 85 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	1 kVA	Cable length	1.5 m
Output power *	1000 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	50 V	LED indicators	Status
Input operation voltage (max) *	150 V	International Protection (IP) code	IP20
Input frequency *	40/70 Hz	Certification	CE, EAC
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	432 J	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	<b>Technical details</b>	
Audible alarm(s)	✓	Sustainability certificates	Green Premium
<b>Ports &amp; interfaces</b>		Compliance certificates	RoHS
USB port	✓	<b>Weight &amp; dimensions</b>	
USB 2.0 ports quantity	1	Width	432 mm
Serial interface	✓	Depth	505 mm
Serial interface type	RJ-45	Height	85 mm
SmartSlot	✓	Weight	21 kg
<b>Battery</b>		Package width	594 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	749 mm
Battery voltage	48 V	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	29.6 kg
Battery recharge time	1 h	<b>Logistics data</b>	
Hot-swap battery	✓	Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000



0731304340263



731304340263

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.