

APC SRT1000RMXLI-NC UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 1000 W

Tuotemerkki : APC Tuotekoodi: SRT1000RMXLI-NC


Tuotteen nimi: SRT1000RMXLI-NC



APC SRT1000RMXLI-NC. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 1000 W. Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 48 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Telineasennettava, Tuotteen väri: musta, Johdon pituus: 1,5 m. Tuotteen leveys: 432 mm, Tuotteen syvyys: 505 mm, Tuotteen korkeus: 85 mm



Features		Design	
Output power capacity * 1 kV. Output power * 1000 Waveform * Sine Input operation voltage (min) * 50 V Input operation voltage (max) * 150	tput power capacity * 1 kVA tput power * 1000 W veform * Sine ut operation voltage (min) * 50 V ut operation voltage (max) * 150 V ut frequency * 40/70 Hz tput operation voltage (min) 220 V tput operation voltage (max) 240 V tput operation voltage (max) 432 J est factor 3:1	Form factor * Cable length Product colour * Display type LED indicators International Protection (IP) code Certification	Rackmount 1.5 m Black LCD Status IP20 CE, EAC
Output operation voltage (min) Output operation voltage (max) Output frequency Surge energy rating Crest factor Emergency Power Off (EPO)		Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -20 - 50 °C 0 - 95% 0 - 95%
Audible alarm(s)	,	Technical details Sustainability certificates	Green Premium
Ports & interfaces USB port USB 2.0 ports quantity Serial interface Serial interface type SmartSlot	1 V RJ-45	Compliance certificates Weight & dimensions Width Depth Height Weight	RoHS 432 mm 505 mm 85 mm 21 kg
Battery Battery technology Battery voltage Battery life (max) Battery recharge time Hot-swap battery	Sealed Lead Acid (VRLA) 48 V 5 year(s) 1 h	Package width Package depth Package height Package weight Logistics data Products per pallet Harmonized System (HS) code	594 mm 749 mm 246 mm 29.6 kg 12 pc(s) 85078000





731304340263

0731304340263

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.