



APC Smart-UPS On-Line, 1500VA/1500W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Brand : APC

Product code: SRT1500XLI

Product name : Smart-UPS On-Line, 1500VA/1500W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Smart-UPS On-Line, 1500VA/1500W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

APC Smart-UPS On-Line, 1500VA/1500W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1500VA on-line tower UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14 input and 6x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. The UPS is compatible with SRTRK4 (4-post) and SRTRK3 (2-post) rail kits sold separately.



Features		Design	
UPS topology *	Double-conversion (Online)	Cable length	1.83 m
Output power capacity *	1.5 kVA	Product colour *	Black
Output power *	1500 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	100 V	International Protection (IP) code	IP20
Input operation voltage (max) *	275 V	Certification	CE, EAC
Input frequency *	40/70 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-20 - 50 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	432 J	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Technical details	
Emergency Power Off (EPO)	✓	Sustainability certificates	Green Premium
Noise level	50 dB	Compliance certificates	RoHS
Audible alarm(s)	✓	Weight & dimensions	
Ports & interfaces		Width	85 mm
USB port	✓	Depth	505 mm
Serial interface	✓	Height	432 mm
Serial interface type	RJ-45	Weight	20.5 kg
SmartSlot	✓	Package width	594 mm
Battery		Package depth	749 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	29.6 kg
Battery recharge time	3 h	Packaging data	
Hot-swap battery	✓	Manual	✓
Design			
Form factor *	Rackmount/Tower		

Logistics data

Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000



0731304340300



731304340300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.