



APC SRT1500XLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1,5 kVA 1500 W

Tuotemerkki : APC

Tuotekoodi: SRT1500XLI

Tuotteen nimi : SRT1500XLI

APC SRT1500XLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 1500 W. Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Johdon pituus: 1,83 m. Tuotteen leveys: 85 mm, Tuotteen syvyys: 505 mm, Tuotteen korkeus: 432 mm



| Features | | Design | |
|---------------------------------|----------------------------|------------------------------------|---------------|
| UPS topology * | Double-conversion (Online) | Cable length | 1.83 m |
| Output power capacity * | 1.5 kVA | Product colour * | Black |
| Output power * | 1500 W | Display type | LCD |
| Waveform * | Sine | LED indicators | ✓ |
| Input operation voltage (min) * | 100 V | International Protection (IP) code | IP20 |
| Input operation voltage (max) * | 275 V | Certification | CE, EAC |
| Input frequency * | 40/70 Hz | Operational conditions | |
| Output operation voltage (min) | 220 V | Operating temperature (T-T) | 0 - 40 °C |
| Output operation voltage (max) | 240 V | Storage temperature (T-T) | -20 - 50 °C |
| Output frequency | 50/60 Hz | Operating relative humidity (H-H) | 0 - 95% |
| Surge energy rating | 432 J | Storage relative humidity (H-H) | 0 - 95% |
| Crest factor | 3:1 | Technical details | |
| Emergency Power Off (EPO) | ✓ | Sustainability certificates | Green Premium |
| Noise level | 50 dB | Compliance certificates | RoHS |
| Audible alarm(s) | ✓ | Weight & dimensions | |
| Ports & interfaces | | Width | 85 mm |
| USB port | ✓ | Depth | 505 mm |
| Serial interface | ✓ | Height | 432 mm |
| Serial interface type | RJ-45 | Weight | 20.5 kg |
| SmartSlot | ✓ | Package width | 594 mm |
| Battery | | Package depth | 749 mm |
| Battery technology | Sealed Lead Acid (VRLA) | Package height | 246 mm |
| Battery life (max) | 5 year(s) | Package weight | 29.6 kg |
| Battery recharge time | 3 h | Packaging data | |
| Hot-swap battery | ✓ | Manual | ✓ |
| Design | | | |
| Form factor * | Rackmount/Tower | | |

Logistics data

| | |
|-----------------------------|----------|
| Products per pallet | 12 pc(s) |
| Harmonized System (HS) code | 85078000 |



0731304340300



731304340300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.