



APC Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT1500RMXLI

Product name : Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit



Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

APC Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Cable length: 1.83 m. Width: 432 mm, Depth: 505 mm, Height: 85 mm




Features		Design	
UPS topology *	Double-conversion (Online)	Cable length	1.83 m
Output power capacity *	1.5 kVA	Product colour *	Black
Output power *	1500 W	Display type	LCD
Waveform *	Sine	LED indicators	Status
Input operation voltage (min) *	50 V	International Protection (IP) code	IP20
Input operation voltage (max) *	150 V	Certification	CE, EAC
Input frequency *	40/70 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-20 - 50 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	432 J	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Technical details	
Emergency Power Off (EPO)	✓	Sustainability certificates	Green Premium
Noise level	50 dB	Compliance certificates	RoHS
Audible alarm(s)	✓	Weight & dimensions	
Ports & interfaces		Width	432 mm
USB port	✓	Depth	505 mm
Serial interface	✓	Height	85 mm
Serial interface type	RJ-45	Weight	21 kg
SmartSlot	✓	Package width	594 mm
Battery		Package depth	749 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	29.6 kg
Battery recharge time	3 h	Packaging data	
Hot-swap battery	✓	Manual	✓
Design		Logistics data	
Form factor *	Rackmount	Products per pallet	12 pc(s)

Logistics data

Harmonized System (HS) code 85078000



0731304340287



731304340287

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date