



APC SRV2KI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2 kVA 1600 W 4 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRV2KI

Tuotteen nimi : SRV2KI

APC SRV2KI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1600 W. Pistorasian tyypit: C13 liitin, Ulostulojen määrä: 4 AC-pistorasia(a), USB-portin tyyppi: USB B-tyyppi. Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 4 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 145 mm, Tuotteen syvyys: 400 mm, Tuotteen korkeus: 238 mm




Features		Battery	
UPS topology *	Double-conversion (Online)	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	2 kVA	Battery recharge time	4 h
Output power *	1600 W	Design	
Waveform *	Sine	Form factor *	Tower
Input operation voltage (min) *	160 V	Product colour *	Black
Input operation voltage (max) *	280 V	Display type	LCD
Input frequency *	40 - 70 Hz	Certification	CE, IEC 62040-1-1, IEC 62040-1-2, REACH
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	600 J	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
ECO mode	✓	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	3%	Non-operating altitude	0 - 14763.6 m
Surge protection	✓	Technical details	
Audible alarm(s)	✓	Compliance certificates	RoHS
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Weight & dimensions	
Ports & interfaces		Width	145 mm
AC outlet types	C13 coupler	Depth	400 mm
AC outlets quantity	4 AC outlet(s)	Height	238 mm
USB port	✓	Weight	16.8 kg
USB 2.0 ports quantity	1	Package width	235 mm
USB port type	USB Type-B	Package depth	525 mm

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Package height	355 mm
Serial interface type	RS-232	Package weight	18.1 kg
RS-232 ports	1	Packaging data	
		Cables included	USB cable
		Manual	✓
		Logistics data	
		Harmonized System (HS) code	85078000



0731304339243



731304339243

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.