



## APC SRV1KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 800 W 3 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRV1KIL

Tuotteen nimi : SRV1KIL

APC SRV1KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 800 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 3 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 4 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 290 mm, Tuotteen syvyys: 400 mm, Tuotteen korkeus: 238 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	1 kVA	<b>Design</b>	
Output power *	800 W	Form factor *	Tower
Waveform *	Pure sine	Product colour *	Black
Input operation voltage (min) *	160 V	Display type	LCD
Input operation voltage (max) *	280 V	LED indicators	✓
Input frequency *	40/70 Hz	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	600 J	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
ECO mode	✓	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	3%	Non-operating altitude	0 - 14763.6 m
Audible alarm(s)	✓	<b>Technical details</b>	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Compliance certificates	RoHS
Auto-restart	✓	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	290 mm
AC outlet types	C13 coupler	Depth	400 mm
Power plug	C14 coupler	Height	238 mm
AC outlets quantity	3 AC outlet(s)	Weight	24 kg
USB port	✓	Battery width	23.5 cm
USB 2.0 ports quantity	1	Battery depth	36.5 cm

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Battery height	33 cm
Serial interface type	RS-232	Battery weight	10.6 kg
Serial ports quantity	1	Packaging data	
SmartSlot	✓	Cables included	USB cable
Battery		Manual	✓
Battery technology	Sealed Lead Acid (VRLA)	Logistics data	
Battery recharge time	4 h	Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337959



731304337959



8592978188047

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.