


## APC SRV1KRI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 800 W 3 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRV1KRI


Tuotteen nimi: SRV1KRI





Features		Ports & interfaces	
UPS topology *	Double-conversion (Online)	Serial ports quantity	1
Output power capacity *	1 kVA	SmartSlot	✓
Output power *	800 W	Battery	
Waveform *	Sine	Battery technology	Sealed Lead Acid (VRLA)
Input operation voltage (min) *	160 V	Battery recharge time	4 h
Input operation voltage (max) *	280 V	Automatic battery test	✓
Input frequency *	40/70 Hz	,	
Output operation voltage (min)	220 V	Design	
Output operation voltage (max)	240 V 50/60 Hz	Form factor *	Rackmount
Output frequency Output voltage regulation	1%	Rack capacity	2U
Surge energy rating	600	Product colour *	Black
Transfer time (Line Mode to Battery	•	Display type	LCD
Mode)	0 ms	LED indicators	✓
Number of input phases	1	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Number of output phases	1		NEXT.
Efficiency	88%	Operational conditions	
Input power factor	0.95	Operating temperature (T-T)	0 - 40 °C
Output power factor	0.8	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
ECO mode	✓	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	×	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	3%	Non-operating altitude  Technical details	0 - 14763.6 m
Noise level	50 dB	Compliance certificates	RoHS
Audible alarm(s)	✓	·	Notis
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Weight & dimensions Width	437 mm
Auto-restart	✓	Depth	312 mm
Maintenance-free	✓	Height	86 mm
Socket circuit breaker	✓	Weight	11 kg
Ports & interfaces		Package width Package depth	455 mm 551 mm
AC outlet types	C13 coupler	Package height	218 mm
Power plug	C14 coupler	Package weight	13.1 kg
AC outlets quantity	3 AC outlet(s)	Packaging data	
USB port	<b>✓</b>		LICE cable
USB port type	USB Type-B	Cables included	USB cable
Serial interface	·	Manual	<b>✓</b>
		Software CD	✓

Logistics data	
Harmonized System (HS) code	85078000
Other features	
Nominal output voltage	230 V
Nominal input voltage	230 V





731304341666

0731304341666

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.