



APC SRV2KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2 kVA 1600 W 4 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRV2KIL

Tuotteen nimi : SRV2KIL

APC SRV2KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1600 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 4 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 335 mm, Tuotteen syvyys: 425 mm, Tuotteen korkeus: 336 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	2 kVA	Product colour *	Black
Output power *	1600 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	160 V	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Input operation voltage (max) *	280 V		
Input frequency *	40/70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Surge energy rating	600 J		
ECO mode	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm		
Auto-restart	✓		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-20 - 50 °C
AC outlets quantity	4 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
USB port	✓	Storage relative humidity (H-H)	0 - 95%
USB 2.0 ports quantity	1	Operating altitude	0 - 3000 m
Serial interface	✓	Non-operating altitude	0 - 14763.6 m
		Technical details	
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	335 mm
		Depth	425 mm
		Height	336 mm
		Weight	45.4 kg
		Battery width	23.5 cm
		Battery depth	35.5 cm
		Battery height	35.5 cm
		Battery weight	18.1 kg

Ports & interfaces		Packaging data	
Serial interface type	RS-232	Cables included	USB cable
Serial ports quantity	1	Manual	✓
SmartSlot	✓	Logistics data	
Battery		Harmonized System (HS) code	85078000
Battery technology	Sealed Lead Acid (VRLA)	Other features	
Battery recharge time	4 h	Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337966



731304337966



8592978188351



7330381238802

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.