


APC SRV2KRI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2 kVA 1600 W 4 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRV2KRI

Tuotteen nimi: SRV2KRI







Features		Ports & interfaces	
UPS topology *	Double-conversion (Online)	Serial ports quantity	1
Output power capacity *	2 kVA	SmartSlot	✓
Output power *	1600 W Sine	Battery	
Waveform *		Battery technology	Sealed Lead Acid (VRLA)
Input operation voltage (min) *	160 V	Battery recharge time	4 h
Input operation voltage (max) *	280 V	Automatic battery test	· · ·
Input frequency * Output operation voltage (min)	40/70 Hz 220 V	,	
Output operation voltage (max)	240 V	Design	_
Output frequency	50/60 Hz	Form factor *	Rackmount
Output voltage regulation	1%	Rack capacity	2U
Surge energy rating	600	Product colour *	Black LCD
Transfer time (Line Mode to Battery	•	Display type	LCD ✓
Mode)	0 ms	LED indicators	
Number of input phases	1	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Number of output phases	1	One wational conditions	
Efficiency	88%	Operational conditions	
Input power factor	0.95	Operating temperature (T-T)	0 - 40 °C
Output power factor	0.8	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95% 0 - 95%
ECO mode	1	Storage relative humidity (H-H) Operating altitude	0 - 95% 0 - 3000 m
Emergency Power Off (EPO)	×		0 - 3000 III
Output voltage Total Harmonic Distortion (THD)	3% 50 dB	Technical details	Dalic
Noise level		Compliance certificates	RoHS
Audible alarm(s)	✓	Weight & dimensions	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Width Depth	437 mm 462 mm
Auto-restart	Jackery alarm, Overload alarm	Height	86 mm
		Weight	18.2 kg
Maintenance-free	•	Package width	551 mm
Socket circuit breaker	✓	Package depth	599 mm
Ports & interfaces		Package height	142 mm
AC outlet types	C13 coupler	Package weight	20.7 kg
AC outlets quantity	4 AC outlet(s)	Packaging data	
USB port	✓ USB Type-B ✓	Cables included	USB cable
USB port type		Manual	✓
Serial interface			
		Software CD	✓
		Logistics data	
		Harmonized System (HS) code	85078000

O +l	har	fast	ures
UL	II EI	ıeaı	ures

Nominal output voltage 230 V Nominal input voltage 230 V





731304341697

0731304341697

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.