

APC SRV6KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 6 kVA 6000 W

Tuotemerkki : APC Tuotekoodi: SRV6KIL

Tuotteen nimi: SRV6KIL


APC SRV6KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 6 kVA, Lähtöteho: 6000 W. Sarjaliitännän tyyppi: RS-232. Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 3 h. Kotelo: Tower, Jäähdytyksen tyyppi: Aktiivinen, Näytön tyyppi: LCD. Tuotteen leveys: 380 mm, Tuotteen syvyys: 485 mm, Tuotteen korkeus: 368 mm





| Features | | Battery | |
|---|--|---|--|
| UPS topology * | Double-conversion (Online) | Battery recharge time | 3 h |
| Output power capacity * | 6 kVA | Automatic battery test | ✓ |
| Output power * Waveform * | 6000 W Pure sine | Design | |
| Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) | 220 V 240 V 40/70 Hz 220 V 240 V | Form factor * Cooling type Display type LED indicators Certification | Tower Active LCD ✓ CE, IEC 62040-1-1, IEC 62040-1-2 REACH |
| Surge energy rating Crest factor | 600 J 3:1 | Operational conditions | NEACH |
| ECO mode Emergency Power Off (EPO) Audible alarm(s) Audible alarm modes | Alarm when on battery, Low battery alarm, Overload alarm | Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude | 0 - 40 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 14763.6 m |
| Auto-restart | • | Technical details | |
| Ports & interfaces | | Compliance certificates | RoHS |
| USB port | ✓ | Weight & dimensions | |
| USB 2.0 ports quantity Serial interface | 1 | Width Depth Height | 380 mm 485 mm 368 mm |
| Serial interface type Serial ports quantity | RS-232 1 | Weight Battery weight | 73 kg 79 kg |

| Ports & interfaces | | Packaging data | |
|-------------------------------------|-------------------------|-----------------------------|-----------|
| Emergency Power Off (EPO) connector | ✓ ✓ | Cables included | USB cable |
| SmartSlot | | Manual | ✓ |
| | | Logistics data | |
| Battery | | Harmonized System (HS) code | 85078000 |
| Battery technology | Sealed Lead Acid (VRLA) | Other features | |
| | | Other leatures | |
| | | Nominal output voltage | 230 V |
| | | Nominal input voltage | 230 V |





731304338024

0731304338024



8592978279851

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.