



# APC Easy UPS On-Line SRV RM 1000 VA 230V with Rail Kit

SRV1KRIRK

Call for More Information +45 88 30 20 10

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, Rack Mounting support rails, User Manual

### Output

Output power capacity	800Watts / 1.0kVA
Max Configurable Power (Watts)	800Watts / 1.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	3%
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Waveform type	Sine wave

### Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 280V
Number of Power Cords	1
Other Input Voltages	220, 240

### Batteries & Runtime

Efficiency	View Efficiency Graph (Available in Technical Tab on site)
------------	--

### Communications & Management

Control panel	Multi-function LCD status and control console
---------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Technical Specifications

### Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

### Physical

Maximum Height	86MM, 8.6CM
Maximum Width	437MM, 43.7CM
Maximum Depth	312MM, 31.2CM
Net Weight	11.0KG
Shipping weight	13.1KG
Shipping Height	218MM, 21.8CM
Shipping Width	455MM, 45.5CM
Shipping Depth	551MM, 55.1CM

### Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-9000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-14763.6meters

### Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs