



APC SRV1KRIRK UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 800 W 3 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRV1KRIRK

Tuotteen nimi : SRV1KRIRK



APC SRV1KRIRK. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 800 W. Virtapistoke: C14 liitin, Ulostulojen määrä: 3 AC-pistorasia(a), Sarjaliitännän tyyppi: RS-232. Kotelo: Telineasennettava, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 437 mm, Tuotteen syvyys: 312 mm, Tuotteen korkeus: 86 mm. Nimellinen lähtöjännite: 230 V, Nimellinen syöttöjännite: 230 V

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	1 kVA	Product colour *	Black
Output power *	800 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	160 V	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Input operation voltage (max) *	280 V		
Input frequency *	40/70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Surge energy rating	600 J		
ECO mode	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Operational conditions	
Power plug	C14 coupler	Operating temperature (T-T)	0 - 40 °C
AC outlets quantity	3 AC outlet(s)	Storage temperature (T-T)	-20 - 50 °C
USB port	✓	Operating relative humidity (H-H)	0 - 95%
USB 2.0 ports quantity	1	Storage relative humidity (H-H)	0 - 95%
Serial interface	✓	Operating altitude	0 - 9000 m
Serial interface type	RS-232	Non-operating altitude	0 - 14763.6 m
Serial ports quantity	1		
SmartSlot	✓		
Battery		Technical details	
Automatic battery test	✓	Compliance certificates	RoHS
		Weight & dimensions	
		Width	437 mm
		Depth	312 mm
		Height	86 mm
		Weight	11 kg
		Battery width	45.5 cm
		Battery depth	55.1 cm
		Battery height	21.8 cm
		Battery weight	13.1 kg
		Packaging data	
		Rack mount kit	✓
		Manual	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304346166



731304346166



8592978154929

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.