



## APC Easy UPS On-Line SRV RM 3000 VA 230V with Rail Kit

SRV3KRIRK

Call for More Information +45 88 30 20 10

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, Rack Mounting support rails, User Manual

| Output                           |                          |
|----------------------------------|--------------------------|
| Output power capacity            | 2.4kWatts / 3.0kVA       |
| Max Configurable Power (Watts)   | 2.4kWatts / 3.0kVA       |
| Nominal Output Voltage           | 230V                     |
| Output Voltage Distortion        | 0%                       |
| Output Frequency (sync to mains) | 50/60Hz +/- 3 Hz         |
| Other Output Voltages            | 220, 240                 |
| Topology                         | Double Conversion Online |
| Waveform type                    | Sine wave                |

| Input                                   |             |
|---|-------------|
| Nominal Input Voltage                   | 230V        |
| Input frequency                         | 40 - 70 Hz  |
| Input Connections                       | IEC-320 C14 |
| Input voltage range for main operations | 160 - 280V  |
| Other Input Voltages                    | 220, 240    |

| Batteries & Runtime |  |
|---------------------|--|
| Efficiency          | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management |  |
|-----------------------------|--|
| Control panel               | Multi-function LCD status and control console  |
| Audible Alarm               | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Technical Specifications

### Surge Protection and Filtering

|                     |           |
|---------------------|-----------|
| Surge energy rating | 600Joules |
|---------------------|-----------|

### Physical

|                 |               |
|-----------------|---------------|
| Maximum Height  | 86MM, 8.6CM   |
| Maximum Width   | 437MM, 43.7CM |
| Maximum Depth   | 632MM, 63.2CM |
| Net Weight      | 27.6KG        |
| Shipping weight | 29.0KG        |
| Shipping Height | 229MM, 22.9CM |
| Shipping Width  | 569MM, 56.9CM |
| Shipping Depth  | 795MM, 79.5CM |

### Environmental

|                             |                 |
|-----------------------------|-----------------|
| Operating Temperature       | 0 - 40 °C       |
| Operating Relative Humidity | 0 - 95 %        |
| Operating Elevation         | 0-3000meters    |
| Storage Temperature         | -20 - 50 °C     |
| Storage Relative Humidity   | 0 - 95 %        |
| Storage Elevation           | 0-14763.6meters |

### Sustainable Offer Status

|       |                       |
|-------|-----------------------|
| RoHS  | Compliant             |
| REACH | REACH: Contains SVHCs |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.