

APC SRV3KRIRK UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2400 W

Tuotemerkki : APC

Tuotekoodi: SRV3KRIRK



230 V

Tuotteen nimi : SRV3KRIRK

APC SRV3KRIRK. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2400 W. Virtapistoke: C14 liitin. Kotelo: Telineasennettava, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 437 mm, Tuotteen syvyys: 632 mm, Tuotteen korkeus: 86 mm. Nimellinen lähtöjännite: 230 V, Nimellinen syöttöjännite: 230 V

| Features | | Design | |
|--|--|---|--|
| UPS topology *Double-conversion (Online)Output power capacity *3 kVAOutput power *2400 WWaveform *SineInput operation voltage (min) *160 VInput operation voltage (max) *280 VInput frequency *40/70 HzOutput operation voltage (min)220 VOutput operation voltage (max)240 VOutput operation voltage (max)240 VSurge energy rating600 J | 3 kVA 2400 W Sine 160 V | Display type LED indicators Certification Operational conditions Operating temperature (T-T) | LCD REACH 0 - 40 °C |
| | 220 V 240 V 50/60 Hz | Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude | -20 - 50 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 14763.6 m |
| ECO mode | Image: A second s | Technical details | |
| Audible alarm(s) | Image: A set of the set of the | Compliance certificates | RoHS |
| Audible alarm modes | Alarm when on battery, Low battery alarm, Overload alarm | Weight & dimensions Width | 437 mm |
| Ports & interfaces | | Depth | 632 mm |
| Power plug USB port USB 2.0 ports quantity Serial interface Serial ports quantity SmartSlot | C14 coupler C14 coupler 1 C14 C14 C14 C14 C14 C14 C14 | Height Weight Battery width Battery depth Battery height Battery weight | 86 mm 27.6 kg 56.9 cm 79.5 cm 22.9 cm 29 kg |
| Battery | | Packaging data | |
| Automatic battery test | Image: A set of the set of the | Rack mount kit Manual | 1 |
| Design | | | • |
| Form factor * Product colour * | Rackmount Black | Logistics data Harmonized System (HS) code Other features | 85078000 |
| | | Nominal output voltage | 230 V |

Nominal input voltage





731304346258

0731304346258



8592978163860

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.