



APC SRVPM2KIL UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2 kVA 1600 W 4 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRVPM2KIL

Tuotteen nimi : SRVPM2KIL

APC SRVPM2KIL. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1600 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 4 h. Kotelo: Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 145 mm, Tuotteen syvyys: 400 mm, Tuotteen korkeus: 238 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery recharge time	4 h
Output power capacity *	2 kVA	Automatic battery test	✓
Output power *	1600 W	Design	
Waveform *	Sine	Form factor *	Tower
Input operation voltage (min) *	160 V	Product colour *	Black
Input operation voltage (max) *	280 V	Display type	LCD
Input frequency *	40/70 Hz	LED indicators	✓
Output operation voltage (min)	220 V	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	600 J	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
ECO mode	✓	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	3%	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 14763.6 m
Audible alarm modes	Low battery alarm, Overload alarm	Technical details	
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	145 mm
Power plug	C14 coupler	Depth	400 mm
AC outlets quantity	4 AC outlet(s)	Height	238 mm
USB port	✓	Weight	16.8 kg
Serial interface	✓		

Ports & interfaces		Weight & dimensions	
SmartSlot	✓	Package width	235 mm
Battery		Package depth	525 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	355 mm
		Package weight	18.1 kg
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304343431



731304343431

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.