



## APC Easy UPS On-Line SRV Ext. Runtime 6000VA 230V, No Battery

SRVPM6KIL

Call for More Information 800 11 62 900

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, USB cable, User Manual

| Output                         |                          |
|--------------------------------|--------------------------|
| Output power capacity          | 6.0kWatts / 6.0kVA       |
| Max Configurable Power (Watts) | 6.0kWatts / 6.0kVA       |
| Nominal Output Voltage         | 230V                     |
| Other Output Voltages          | 220, 240                 |
| Load Crest Factor              | 3 : 1                    |
| Topology                       | Double Conversion Online |
| Waveform type                  | Sine wave                |

| Input                 |                  |
|-----------------------|------------------|
| Nominal Input Voltage | 230V             |
| Input frequency       | 40 - 70 Hz       |
| Input Connections     | Hard Wire 3-wire |
| Other Input Voltages  | 220, 240         |

| Batteries & Runtime   |  |
|-----------------------|--|
| Battery type          | No internal battery - uses external battery system |
| Typical recharge time | 3hour(s)   |

| Communications & Management |  |
|-----------------------------|--|
| Control panel               | Multi-function LCD status and control console  |
| Audible Alarm               | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Technical Specifications

### Communications & Management

|                           |     |
|---------------------------|-----|
| Emergency Power Off (EPO) | Yes |
|---------------------------|-----|

### Surge Protection and Filtering

|                     |           |
|---------------------|-----------|
| Surge energy rating | 600Joules |
|---------------------|-----------|

### Physical

|                 |                   |
|-----------------|-------------------|
| Maximum Height  | 336MM, 33.6CM     |
| Maximum Width   | 190MM, 19.0CM     |
| Maximum Depth   | 374MM, 37.4CM     |
| Net Weight      | 13.0KG            |
| Shipping weight | 16.0KG            |
| Shipping Height | 460MM, 46.0CM     |
| Shipping Width  | 290MM, 29.0CM     |
| Shipping Depth  | 12471MM, 1247.1CM |

### Environmental

|                             |                           |
|-----------------------------|---------------------------|
| Operating Temperature       | 0 - 40 °C                 |
| Operating Relative Humidity | 0 - 95 (non-condensing) % |
| Operating Elevation         | 0-3000meters              |
| Storage Relative Humidity   | 0 - 95 (non-condensing) % |
| Storage Elevation           | 0-14763.6meters           |

### Conformance

|                   |                                  |
|-------------------|----------------------------------|
| Approvals         | CE, IEC 62040-1-1, IEC 62040-1-2 |
| Standard warranty | 2 years repair or replace        |

### Sustainable Offer Status

|       |                          |
|-------|--------------------------|
| RoHS  | Compliant                |
| REACH | REACH: Contains No SVHCs |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.