

APC SRVPM6KRI uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 6000 W

Brand : APC Product code: SRVPM6KRI

Product name: SRVPM6KRI



- USB connection: Use your PC to access additional power protection and management features for your UPS via a USB Port
- Allows the user to manage the UPS functions, schedule automatic shutdown and monitor the power grid occurrences through an interactive interface that ensures an easy and intuitive monitoring
- Safety-agency approved: Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment
- Pure sine wave output on battery: Simulates utility power to provide the highest degree of compatibility for active PFC (power factor corrected) servers and sensitive electronics Easy UPS On-Line SRV RM Extended Runtime 6000VA 230V No Battery



Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	6 kVA	Design	
Output power * Waveform * Input frequency * Output operation voltage (min) Output operation voltage (max) Surge energy rating Crest factor ECO mode Emergency Power Off (EPO) Audible alarm(s)	6000 W Pure sine 40/70 Hz 220 V 240 V 600 J 3:1 Alarm when on battery, Low battery	Form factor * Rack capacity Product colour * Display type LED indicators Certification Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	Rackmount 2U Black LCD ✓ CE, IEC 62040-1-1, IEC 62040-1-2 REACH 0 - 40 °C 0 - 95%
Audible alarm modes	alarm, Overload alarm	Storage relative humidity (H-H)	0 - 95%
Auto-restart	✓	Operating altitude Non-operating altitude	0 - 3000 m 0 - 14763.6 m
Ports & interfaces		. 5	0 - 14703.0 III
Power plug USB port USB 2.0 ports quantity	Terminal ✓ 1	Technical details Compliance certificates Weight & dimensions	RoHS
USB port type Serial interface Serial ports quantity Emergency Power Off (EPO) connector SmartSlot	USB Type-B ✓ 1 ✓	Width Depth Height Weight Package width Package depth	438 mm 615 mm 87 mm 14 kg 600 mm 760 mm
Battery		Package height	240 mm
Battery technology Battery recharge time	Sealed Lead Acid (VRLA) 3 h	Package weight	18 kg

Packaging data Cables included USB cable Manual ✓





731304343462

0731304343462

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.