



APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery



Brand : APC

Product code: SRTL2200RMXLI-NC

Product name : Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

[APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:](#)

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 2200VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with BS1363A British, IEC 320 C20, and Schuko CEE 7/EU1-16P inputs, 6x IEC 320 C13 and 2x IEC 320 C19 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	2.2 kVA	Rack capacity	3U
Output power *	1980 W	Cable length	1.83 m
Waveform *	Sine	Product colour *	Black, Silver
Input operation voltage (min) *	160 V	Control type	Buttons
Input operation voltage (max) *	275 V	Display type	LCD
Input frequency *	40 - 70 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	Certification	CE, EAC
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Surge energy rating	432 J		
Crest factor	3:1		
Output voltage Total Harmonic Distortion (THD)	2%		
Noise level	50 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto shut-off	✓		
Power source type	AC		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler, C19 coupler	Operating temperature (T-T)	0 - 40 °C
AC outlets quantity	8 AC outlet(s)	Storage temperature (T-T)	-20 - 50 °C
Emergency Power Off (EPO) connector	✓	Operating relative humidity (H-H)	0 - 95%
Battery		Technical details	
Battery technology	Lithium-Ion (Li-Ion)	Sustainability certificates	Green Premium
Battery voltage	48 V		
Battery life (max)	10 year(s)		
Battery recharge time	4 h		
		Weight & dimensions	
		Width	432 mm
		Depth	639 mm
		Height	128 mm
		Weight	30.5 kg
		Package width	870 mm
		Package depth	600 mm
		Package height	245 mm
		Package weight	41.4 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	Output power cable, USB cable
		Manual	✓
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Bypass	Built-in



0731304347545



731304347545



8592978146061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.