

## APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithiumion external battery



Brand: APC Product code: SRTL2200RMXLI-NC

**Product name :** Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery




Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 2200VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with BS1363A British, IEC 320 C20, and Schuko CEE 7/EU1-16P inputs, 6x IEC 320 C13 and 2x IEC 320 C19 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCl clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features		Design	
Double-conversion (Online)  Dutput power capacity * 2.2 kVA  Dutput power * 1980 W  Waveform * Sine  Input operation voltage (min) * 160 V  Input operation voltage (max) * 275 V  Input frequency * 40 - 70 Hz  Dutput operation voltage (min) * 220 V	Form factor * Rack capacity Cable length Product colour * Control type Display type International Protection (IP) code Certification	Rackmount 3U 1.83 m Black, Silver Buttons LCD IP20 CE, EAC	
Output operation voltage (max)	240 V	Operational conditions	
Output frequency Surge energy rating Crest factor	50/60 Hz 432 J 3:1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 50 °C 0 - 95%
Output voltage Total Harmonic Distortion (THD)	2%	Technical details	
Noise level	50 dB	Sustainability certificates	Green Premium
Surge protection	✓	Weight & dimensions	
Audible alarm(s) Auto shut-off Power source type	✓ ✓ AC	Width Depth Height	432 mm 639 mm 128 mm
Ports & interfaces		Weight	30.5 kg
AC outlet types AC outlets quantity Emergency Power Off (EPO) connector	C13 coupler, C19 coupler 8 AC outlet(s)	Package width Package depth Package height Package weight	870 mm 600 mm 245 mm 41.4 kg
Battery		Packaging data	
Battery technology Battery voltage Battery life (max) Battery recharge time	Lithium-lon (Li-lon) 48 V 10 year(s) 4 h	Rack mount kit Cables included Manual Quick installation guide  Logistics data	Output power cable, USB cable
		Harmonized System (HS) code	03070000

Other features	
Bypass	Built-in





731304347545

0731304347545



8592978146061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.