



## APC SRTL1000RMXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 1 kVA 900 W 8 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SRTL1000RMXLI


**Tuotteen nimi :** SRTL1000RMXLI

APC SRTL1000RMXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun kestoikä (maks.): 10 vuosi/vuosia, Akun latausaika: 6 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 3U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 590 mm, Tuotteen korkeus: 128 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	1 kVA	Cold start	✓
Output power *	900 W		
Waveform *	Sine		
Input operation voltage (min) *	220 V		
Input operation voltage (max) *	240 V		
Input frequency *	40/70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Surge energy rating	340 J		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Noise level	50 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Rackmount
Power plug	C14 coupler	Rack capacity	3U
AC outlets quantity	8 AC outlet(s)	Product colour *	Black, Grey
USB port	✓	Display type	LCD
Serial interface	✓	LED indicators	Status
Serial interface type	RJ-45	International Protection (IP) code	IP20
Serial ports quantity	1	Certification	CE, EAC, RCM, VDE
SmartSlot	✓		
Battery		Operational conditions	
Battery technology	Lithium-Ion (Li-Ion)	Operating temperature (T-T)	0 - 40 °C
Battery life (max)	10 year(s)	Storage temperature (T-T)	-20 - 50 °C
Battery recharge time	6 h	Operating relative humidity (H-H)	0 - 95%
Hot-swap battery	✓	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	432 mm
		Depth	590 mm
		Height	128 mm
		Weight	26.7 kg
		Package width	600 mm
		Package depth	850 mm
		Package height	445 mm
		Package weight	37.4 kg
		Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V



0731304346388



731304346388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.